



CMBUS-24

CMBUS-24, M-Bus to Modbus Converter,

Code: M540B0. DESCATALOGADO

Specifications

DC power supply	
Consumption	55 mA
Nominal voltage	18 30 Vdc
Mechanical characteristics	
Size (mm) width x height x depth	17.5 x 90 x 58 (mm)
Weight (kg)	0,134
Communication Network	
Protocol	Modbus RTU / M-BUS
Technology / Interface	M-BUS
Standards	
Electrical safety, Maximum height (m)	2,000
Standards	EN 61000-6-3+A1,EN 61000-6-2, IEC 61000-4-3, IEC 61000-4-2, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, EN 61010-1, LVD 73/23/EEC, EMC 89/336/EEC, CE 93/68/EEC
User interface	
LED	HOST LED / M-BUS LED
Serial communication	
Technology / Type	RS-232 / RS-485

CMBUS

M-Bus to Modbus Converter

CODE	TYPE	Description
M-BUS		
D80208.	CMBUS-8	M-Bus to Modbus-RTU Converter, up to 8 Mbus slaves







CMBUS-24

M-Bus to Modbus RTU conversion gateway

Code: M540B0.

Connections Dimensions





