



CVM-C5-MC-IC

Code: M55873. **DESCATALOGADO**

- > Power analyzer
- > Transistor output: 1
- > Digital inputs: 1
- > Measuring current Channels: 3
- > Input current: .../250 mA
- > Mounting: Pannel

Description

The CVM-C5 is a panel mounted (96 x 96 mm) multimeter that records energy values. Compact and intuitive, with 4-quadrant measurement (Consumption and Generation). The CVM-C5 is suitable for Low Voltage installations, in both 3 and 4-wire three-phase circuits, two-phase circuits with or without neutral, singlephase circuits or ARON connections.

Display features and interface:

- o Quick display of parameters with a single button
- o Clearly displays the electric parameters of the installation
- o Displays the electricity consumption value according to the cost per kWh
- o kgCO2 consumption/generation indicator or according to the energy source
- o Backlit LCD screen
- $\circ \;\;$ Operating hour indicator for preventive maintenance.

Other features:

- Modbus/RS-485 communications (optional)
- Measurement with CIRCUTOR's MC efficient current transformers or .../5 A, .../1 A or .../333 mV transformers.
- 1 digital output (S0 interface)
- o 1 digital input (tariff or energy source selection)
- o Maximum, minimum values and maximum demand.

Application

- Recording and displaying the consumption of energy from two different sources (network/generator set).
- o Generation of an impulse signal associated with the cost, kgCO2 emissions or savings, according to the consumption or generation of energy.
- o Generation of alarms with a transistor output; configurable parameters: Low/High, hysteresis (%), NO/NC, connection/disconnection delay and interlocking.







Multifunctional multimeter for panel

Code: M55873.

Specifications

AC power supply	
Installation category	CAT III 300 V
Consumption	3.5 6 VA
Frequency	50 60 Hz
Nominal voltage	95 240 V ~ ± 10%
DC power supply	
Installation category	CAT III 300 V
Consumption	2 6 W
Nominal voltage	105 272 Vdc ± 10%
Mechanical characteristics	
Size (mm) width x height x depth	96 x 96 x 60.9 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	Panel
Weight (kg)	0,2
Environmental characteristics	
Protection class	IP 51 (Front), IP 20 (rear)
Relative humidity (without condensation)	595%
Storage temperature	-10 +50 °C
Working temperature	-5+45 °C
Standards	
Certifications	UL/CSA 61010-1 3rd edition
Electrical safety, Maximum height (m)	2000
Standards	IEC 61010, UNE EN 61000-6-2, UNE EN 61000-6-4,
Current measurement circuit	
Installation category	CAT III 300 V
Nominal current (In)	/250A
Phase current measuring range	5110% In
Maximum pulse current	100 A
Minimum current measurement	0,25 A (MC1) / 0,12 A (MC3)
Voltage measurement circuit	
Installation category	CAT III 300 V
Frequency measuring range	45 65 Hz
Voltage measuring range	5120% Un



Page 2 of 4





Multifunctional multimeter for panel

Code: M55873.

Nominal voltage	300V Ph-N, 520V Ph-Ph
Minimum measurement voltage (Vstart)	10 V Ph-N
User interface	
Keyboard	3 keys
Display type	LCD
Visible display area size	60X54 mm
Digital inputs	
Input/output insulation	Optoisolated
Quantity	1
Туре	Potential-free contact
Digital transistor outputs	
Pulse width	100 ms
Quantity	1
Туре	NPN
Pulse output, time period (Ton / Toff)	100 ms/100 ms
Maximum frequency	5 imp / s
Maximum current	50 mA
Maximum voltage	24 Vdc
Measurement accuracy	
Phase voltage measurement	0,50%

⁴⁻quadrant measuring unit. Can be used to program the voltage transformer ratio







Multifunctional multimeter for panel

Code: M55873.

Dimensions





