



CVM-D41 DC V, Digital multimeter DIN rail, 2 output relays

Code: M5663A0040000 CONSULTAR DISPONIBILIDAD

> Protocol: Modbus/RTU

> Módules: 6

> IP: 54

> Communications: RS-485

> N° relays: 2

> Digital inputs: 2

> Analog output: 1 (0 ... 10V)

> System: DC (Shunt)

> Measurement Range (V): ± 150 / 300 /600 / 1000 / 1500 Vdc

> Measurement Range (A): 50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV

> Parameters: V/A/kW/kWh dc

> Mounting: DIN Rail

Description

The CVM-D41 DC is a digital power analyzer for installing on a DIN rail. Its screens are operated using buttons to display different electrical parameters in a DC network of up to 1500 VDC, such as voltage, current, power and energy (A·h).

This analyzer has the following key features:

- o DIN rail installation.
- $\circ~$ DC voltage measurement up to 1500VDC CATIIII
- O Shunt current measurement
- 2 digital inputs + 2 relay outputs + 1 analogue output (0/4...20 mA) or (0 / 2 ... 10 Vdc), depending on the model
- LED status indicator
- o RS-485 communications (Modbus/RTU)
- o Configuration via Power Studio SCADA

Application

Measurement and management of installations with a DC power supply:

- Industrial Applications
- $\circ \ \ \mathsf{Electric} \ \mathsf{vehicle} \ \mathsf{charging} \ \mathsf{points}$
- o Self-supply systems
- O Solar photovoltaic Installations
- HVAC
- o Industrial process control







Digital instruments: Programmabled DC measurement Central

Code: M5663A0040000

Specifications

AC power supply	
Installation category	CAT III 300V
DC power supply	
Installation category	CAT III 300 V
Consumption	2.5 4.5 W
Nominal voltage	20 60 Vdc
Mechanical characteristics	
Size (mm) width x height x depth	108 x 117.43 x 74 (mm)
Weight (kg)	0,7
Environmental characteristics	
Relative humidity (without condensation)	≤ 93 %
Storage temperature	-25 +70 °C
Working temperature	-25 +70 °C
Current measurement circuit	
Installation category	CAT III 1500 V
Consumption	<1VA
Nominal current (In)	Shunt: 50 / 60 /75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV
Allowable overload	1.2 In continuous (max.1500 Vdc)
Voltage measurement circuit	
Installation category	CAT III 1500 V
Consumption	<1VA
Nominal voltage	± 150 / 300 / 600 / 1000 / 1500 Vdc
Maximum permanent measurement voltage	1.2 Un continuous
Standards	
Electrical safety, Maximum height (m)	2000
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-6, IEC 61000-4-11, IEC 61010-1, IEC 61326-1, IEC 61010-2-030
User interface	
Display type	LCD 5 digits
Digital inputs	







Digital instruments: Programmabled DC measurement Central

Code: M5663A0040000

Input/output insulation	4000 V ~
Quantity	2
Туре	Potential-free contact
Maximum short-circuit current	3.3 mA dc
Maximum open circuit voltage	17 V dc

Analogue outputs

Quantity	1
Linearity	0.5 %
Current mode: maximum load resistance	350 Ω
Voltage mode: nominal output range	0 / 2 10 Vdc
Maximum internal voltage	17 V dc

Digital relay outputs

Quantity	2
Maximum current	2.5 A
Electrical life	1 x 10 ⁵ (250 V~ / 5A)
Maximum switching capacity	625 VA

Measurement accuracy

Phase current measurement	Class 0.5
Active energy measurement (kWh)	Class 1
Active power measurement (kW)	Class 1
Phase voltage measurement	Class 0.5

Serial communication

Protocol	ModBus RTU
Technology / Type	RS-485

CVM-D41 DC

Programmable DC measurement device

CODE	TYPE	System	Measurement Range (V)	Measurement Range (A)	N° relays	Digital inputs	Analog output	Módules	Protocol
Multimeter									
M56638.	CVM-D41 DC mA	DC (Shunt)	± 150 / 300 /600 / 1000 / 1500 Vdc	50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV	2	2	1 (20 mA)	6	Modbus/RTU
M566380040000	CVM-D41 DC mA	DC (Shunt)	± 150 / 300 /600 / 1000 / 1500 Vdc	50 / 60 / 75 / 100 / 150 / 200 / 250 / 300 / 400 / 600 mV	2	2	1 (20 mA)	6	Modbus/RTU



Page 3 of 4





Digital instruments: Programmabled DC measurement Central

Code: M5663A0040000

Dimensions Connections





