



## Line-M-3G

Line-M-3G, 3G communications modem and Bus-Line to communicate with the Line-EDS devices,

Code: M58E05. (CONSULTAR DISPONIBILIDAD)

### Specifications

#### AC power supply

Installation category	CAT III 300V
Consumption	2,8 ... 4,1 VA
auxiliary power supply mode	Through the line-EDS device

#### DC power supply

Consumption	1,9 ... 2,2 W
-------------	---------------

#### Mechanical characteristics

Size (mm) width x height x depth	52.5 x 96.95 x 88.75 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail (IEC 60715)
Weight (kg)	0,15

#### Environmental characteristics

Protection class	IP30, Front: IP40
Relative humidity (without condensation)	5 ... 95%
Storage temperature	-20 ... +70 °C
Working temperature	-10 ... +50 °C

#### Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Standards	UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4

#### User interface

LED	4 LED
-----	-------

#### Radio communication -Antenna

	SMA (Right Angle)
--	-------------------

#### Radio communication

Band	850/900/1700/1800/1900/2100 MHz
Technology / Type	3G

#### Line-M-3G

Expansion modules, Line series



## Line-M-3G

Code: M58E05.

CODE	TYPE	Description
<b>Modem</b>		
D73007.	Line-M-3G	3G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices

3G Modem, expansion modules, Line system



## Line-M-3G

Code: M58E05.

### Dimensions



### Connections

