



## EDS

---

EDS, Efficiency Data Server

Code: M61010.

- > Servidor
- > Protocol: Modbus Circuitor
- > Communications: Ethernet
- > N° relays: 6
- > Digital inputs: 8

## Description

---

EDS is an energy manager equipped with **PowerStudio** Embedded and a built-in web and XML server, which enables the user to query any electrical variable by connecting the metering equipment to its RS-485 bus without having to install any software. Thanks to the RS-485 expansion bus, the user can view any variable from the units connected to the bus and can even display information in real time, in table or graphic format (data logger). There are 8 voltage-free digital inputs and 6 programmable relay digital outputs.

Its most salient features include:

- Parameterisation and management of automatic events
- Alarm recording system and system event management
- E-mail alarms.
- RS-485 port for connecting up to 5 **CIRCUITOR** devices.
- Ethernet connection
- Centralisation of alarms through detection of logical states or centralization of consumption by pulses.

## Application

---

**Domestic application:** EDS can be used to control the partial consumption of each load in a domestic installation.

- Control of domestic consumption.
- Compare your consumption with that of the energy marketer.
- Rationalisation of home consumption.

**SME/Industrial application:** EDS facilitates the control of partial consumptions of the different single-phase and three-phase loads during productive and non-productive periods.

- Control the consumption of your installation 24/365 and locate residual consumption during non-production periods.
- Check the power level contracted in the installation.
- Supervise the level of harmonics and the reactive load of your installation.
- Alarms for consumption or incidents in your electrical network.
- No need for a computer
- Possibility of connection when specified: the system acts automatically.
- Provides information about your bill before you receive it.

**Multi-point application:** in the case of load distribution (or remote installations) EDS can control the individual consumption of each of the installations and centralise them into a single one.

- Efficient, easy and simple control of the consumption of your remote sites.
- Energy reports per consumption zone or site
- Remote alarms for excess consumption or incidents in the electrical network.



## EDS

---

Efficiency Data Server

Code: M61010.

- Possibility of comparing consumption for each site.



## EDS

Efficiency Data Server

Code: M61010.

### Specifications

#### AC power supply

Consumption	5...8VA
Frequency	47...63 Hz
Nominal voltage	85...264 Vca/120...300 Vcc

#### Mechanical characteristics

Size (mm) width x height x depth	90 x 105 x 105 (mm)
Envelope	Plastic UL 94 - V0 self-extinguishing
Weight (kg)	0,29

#### Environmental characteristics

Protection class	IP 20
Relative humidity (without condensation)	5...95%
Working temperature	-10 ... +60 °C

#### Standards

Certifications	CE, UL
Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III , IEC 61010
Standards	UL 94, UNE-UNE-EN 61010-1, UNE-EN55011, UNE-EN 6100-4-2, UNE-EN 61000-4-3, UNE-EN 61000-4-11, UNE-EN 61000-6-4, UNE-EN 61000-6-2, UNE-EN61000-6-3, UNE-EN 61000-4-5

#### Communication Network

Protocol	HTTP / Modbus RTU
Technology / Type	Ethernet 10 /100 BT

#### Electrical safety

Insulation	Double-insulated electric shock protection class II (IEC 61010-1)
------------	---

#### User interface

Display format	Alphanumeric 2 Lines
Resolution of the display	20 characters
Display type	Backlit LCD

#### Digital inputs

Input/output insulation	1,5 kV
Type	Free of optoisolated voltage
Maximum short-circuit current	50 mA



## EDS

Efficiency Data Server

Code: M61010.

### Digital relay outputs

Quantity	6
Maximum current	5A
Maximum open contact voltage	250 V ~
Electrical life	$3 \times 10^4$ (250 Vca / 5 A)
Mechanical life	$2 \times 10^7$
Maximum switching capacity	750 VA

Energy device with embedded PowerStudio technology: Built-in web and XML server, RS-485 Modbus expansion bus, Ethernet 10/100 Base/TX connection, 6 modules mounted on a DIN rail



## EDS

---

Efficiency Data Server

Code: M61010.

## Dimensions

---

