

SBOX 3G NET

SBOX 3G NET, Gateway with 3G communications (SIM card must be provided by the user) to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to Electrical Energy Efficiency,

Code: M61930. **CONSULTAR DISPONIBILIDAD**

Specifications

Mechanical characteristics

Weight (kg)	0,414

Line-M

Expansion modules, Line system

CODE	TYPE	Integrated Software	Transistor output	Generic Modbus	Communications	Protocol	Description	Analogue Inputs	N° relays	Digital inputs	Analog output
D70050.	Line-EDS-cloud	API's de	2	1	Ethernet | RS-485 | Bus-Line	Modbus | API's | web					
D70005.	Line-EDS-PS	PowerStudio	2	1	Ethernet | RS-485 | Bus-Line	Modbus (Circutor + generic) | XML					
D70020.	Line-EDS-PSS PRO	PowerStudio Scada PRO	2	1	Ethernet | RS-485 | Bus-Line	Modbus (Circutor + generic) | XML					
D70021.	Line-EDS-iMonitor	PowerStudio Scada PRO + Front-end iMonitor	2	1	Ethernet | RS-485 | Bus-Line	Modbus (Circutor + generic) | XML					
Modem											
D7300C.	Line-M-4G						4G/GPRS communications modem and Bus-Line to communicate with Line-EDS devices				
Ethernet converter											
D80030.	Line-TCPRS1						RS-485/RS-232 to Ethernet/Wi-Fi converter (ModbusTCP/TCP/UDP) Integrated web server and mobile app (MyConfig) for configuration				
Power supply											
D7300A.	Line-M-EXT-PS						110-277 V ~ (P-N)/110-480 V ~ (P-P) power supply for maximum of 3 Line devices				
Input/Output Modules											
D73001.	Line-M-4IO-T		4			Modbus RTU		-	-	4	-
D73002.	Line-M-4IO-R		-			Modbus RTU		-	4	4	-
D73008.	Line-M-8I6O		-			Modbus RTU		-	6	8	-
D73003.	Line-M-4IO-A		-			Modbus RTU		4 (0/4 ... 20 mA)	-	-	4 (0/4 ... 20 mA) |4 (0/2 ... 10 Vdc)
D73004.	Line-M-4IO-RV		-			Modbus RTU		-	4	4 (230 V)	-
D73006.	Line-M-20I					Modbus RTU			-	20	



SBOX 3G NET

Code: M61930.

CODE	TYPE	Integrated Software	Transistor output	Generic Modbus	Communications	Protocol	Description	Analogue Inputs	N° relays	Digital inputs	Analog output
D60060.	ePick GPRS VPN						Gateway with GPRS communications via VPN network (1) and SIM card fully configured to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to electrical energy efficiency				
D60070.	ePick GPRS NET						Gateway with GPRS communications (SIM card must be provided by the user) to send data from the units connected to the RS-485 port or Ethernet to the Databox cloud platform in order to carry out energy audits and improvements related to Electrical Energy Efficiency				

Creation date: 21/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.