

TCPRS1+, RS-485 / Ethernet converter / Wi-Fi

Code: M62422. DESCATALOGADO

> Protocol: TCP/IP | UDP | Modbus TCP/IP | HTTP (Web server)

> Communications: Ethernet, Wi-Fi

Description

The **TCPRS1+** is a gateway designed to convert a physical environment (RS-485) to Ethernet and/or Wi-Fi. The device features a Web Server and the **"MyConfig Wifi"** app (Android), from which the user can fully edit the configuration parameters of the device.

Other features:

- The device is for installation inside a medium or low voltage electric panel or enclosure, with DIN rail mounting (IEC 60715).
- $\circ~$ The TCPRS1+ comes with DHCP enabled by default.
- \circ Connect up to 32 devices on the RS-485 communications bus.

Application

For any installation that has multiple RS-485 communications devices that require monitoring via Wi-Fi or Ethernet.

Circutor



RS-485 to Ethernet converter / Wi-Fi

Code: M62422.

Specifications

Installation category	CAT III
Consumption	2 7 VA
Frequency	50 60 Hz
Nominal voltage	100 264 V ~
DC power supply	
Installation category	CAT III
Consumption	1,6 2 W
Nominal voltage	120 300 Vdc
Mechanical characteristics	
Size (mm) width x height x depth	35 x 109.45 x 70 (mm)
Envelope	Self-extinguishing VO plastic
Fastening	DIN rail
Weight (kg)	0,126
Environmental characteristics	
Protection class	IP30, Front: IP40 IK08
Relative humidity (without condensation)	5 95%
Storage temperature	-20 +70 °C
Working temperature	-20 +60 °C
Communication Network	
Protocol	TCP/IP UDP Modbus TCP/IP HTTP (Web server)-REST
Technology / Type	Ethernet
Standards	
Electrical safety, Maximum height (m)	2000
Standards	EN 62368-1:2020/A11:2020/AC:2020-05, EN 50663: 2017, ETSI EN 301 489- V2.2.3, ETSI EN 301 489-17 V3.2.4, ETSI EN 301 893 V2.1.1
User interface	
LED	6 LED
Serial communication	
Technology / Type	RS-485
Wireless communication	



RS-485 to Ethernet converter / Wi-Fi

Code: M62422.

Technology / Type

Wi-Fi

TCPRS1+

RS-485 / Ethernet / Wi-Fi converter

CODE	ТҮРЕ	Communications	Protocol
Ethernet			
D80010.	TCPRS1+	RS-485, Ethernet, Wi-Fi	TCP/IP UDP Modbus TCP/IP HTTP (Web server)
D80011.	TCPRS1+PSDC	RS-485, Ethernet, Wi-Fi	TCP UDP Modbus TCP HTTP (Web server)-REST

Circutor



RS-485 to Ethernet converter / Wi-Fi

Code: M62422.

Dimensions

Connections

×

×

