



Kit line-TCPRS1/M-20I, Pulse and contact centraliser

Code: M62510.

> Protocol: ModbusTCP | TCP | UDP

> Módules: 6

> Communications: Ethernet | WiFi

> Digital inputs: 20

Description

Pulse centralizing device to fully manage the consumption of any installation. It can send data to a higher-Ievel SCADA system thanks to the line-TCPRS1 gateway, which incorporates Wi-Fi and Ethernet communications.

Application

Manage consumption in:

- Shopping centres
- o Flats
- o Industry
- o Ports and campgrounds







Impulse centralizer kits

Code: M62510.

Specifications

CAT III 300 V
7 11 VA
50 60 Hz
100 264 V ~
CAT III 300 V
5,5 6 W
100 300 Vdc
105 x 118 x 70 (mm)
Self-extinguishing V0 plastic
DIN rail
0,3
IP30, Front: IP40
5 95%
-20 +70 °C
-10 +50 °C
RJ-45
TCP / UDP / Modbus TCP / Web server - HTTP / REST
Ethernet 10 /100 BT
2000
CAT III 300V
UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4
28 LED
4,2 kVdc
20







Impulse and contact centralisers

Impulse centralizer kits

Code: M62510.

Consumption (per input)	60 mA inputs OFF / 240 mA inputs ON
Туре	Optocoupled
Wireless communication	
Band	2,4 GHZ. IEEE 802.11 b: 20 dBm / IEEE 802.11 n: 14 dBm
Technology / Type	Wi-Fi

Kit Line-TCPRS1/M

Impulse and contact centralisers

CODE	ТҮРЕ
M62510.	Kit line-TCPRS1/M-20I
M62520.	Kit line-TCPRS1/2xM-20I







Impulse centralizer kits

Code: M62510.

Dimensions





Page 4 of 4