



Kit line-TCPRS1/2xM-20I, Pulse and contact centraliser

Code: M62520.

> Protocol: ModbusTCP | TCP | UDP

> Módules: 9

> Communications: Ethernet | WiFi

> Digital inputs: 40

#### Description

Pulse centralizing device to fully manage the consumption of any installation. It can send data to a higher-Ievel SCADA system thanks to the line-TCPRS1 gateway, which incorporates Wi-Fi and Ethernet communications.

#### **Application**

Manage consumption in:

- Shopping centres
- o Flats
- o Industry
- o Ports and campgrounds







Impulse centralizer kits

Code: M62520.

### **Specifications**

| AC power supply                          |  |
|--|--|
| Installation category                    | CAT III 300 V                                      |
| Consumption                              | 10,5 14,5 VA                                       |
| Frequency                                | 50 60 Hz   |
| Nominal voltage                          | 100 264 V ~  |
| DC power supply                          |  |
| Installation category                    | CAT III 300 V                                      |
| Consumption                              | 9 9,5 W  |
| Nominal voltage                          | 100 300 Vdc  |
| Mechanical characteristics               |  |
| Size (mm) width x height x depth         | 158 x 118 x 70 (mm)                                |
| Envelope                                 | Self-extinguishing V0 plastic                      |
| Fastening                                | DIN rail   |
| Weight (kg)                              | 0,43   |
| Environmental characteristics            |  |
| Protection class                         | IP30, Front: IP40                                  |
| Relative humidity (without condensation) | 5 95%  |
| Storage temperature                      | -20 +70 °C   |
| Working temperature                      | -10 +50 °C   |
| Communication Network                    |  |
| Connection mechanism                     | RJ-45  |
| Technology / Type                        | Ethernet 10 /100 BT                                |
| Standards                                |  |
| Electrical safety, Maximum height (m)    | 2000   |
| Electrical safety, Installation category | CAT III 300V                                       |
| Standards                                | UNE-EN 61010-1, UNE-EN 61000-6-2, UNE-EN 61000-6-4 |
| User interface                           |  |
| LED                                      | 49 LED   |
| Digital inputs                           |  |
| Input/output insulation                  | 4,2 kVdc   |
| Quantity                                 | 40   |
| Consumption (per input)                  | 60 mA inputs OFF / 240 mA inputs ON                |
|  |  |







Impulse centralizer kits

Code: M62520.

| Туре                   | Optocoupled  |
|------------------------|--|
| Wireless communication |  |
| Band                   | 2,4 GHZ. IEEE 802.11 b: 20 dBm / IEEE 802.11 n: 14 dBm |
| Technology / Type      | Wi-Fi  |

#### Kit Line-TCPRS1/M

Impulse and contact centralisers

| CODE    | ТҮРЕ                    |
|---------|-------------------------|
| M62510. | Kit line-TCPRS1/M-20I   |
| M62520. | Kit line-TCPRS1/2xM-20I |







Impulse centralizer kits

Code: M62520.

# **Dimensions**



