

CIRLAMP NODO DN



CIRLAMP NODO DN

Code: M63021. (CONSULTAR DISPONIBILIDAD)

> For managing the lights with 2-level electronic ballasts / drivers (lamp power of up to 600 W)

Specifications

AC power supply

Installation category	CAT III 300 V
Consumption	2 W / 16 VA
Frequency	50 / 60 Hz
Nominal voltage	184 ... 276 Vca (Autoalimentado)

Current measurement circuit

Installation category	CAT III 300 V
Phase current measuring range	0,1 ... 3 A
Minimum current measurement	0,08 A

Voltage measurement circuit

Installation category	CAT III 300 V
Input impedance	600 MΩ
Voltage measuring range	184 ... 276 Vac

Electrical characteristics

Insulation voltage, circuit	4 kV RMS 50 Hz durante 1 minuto
-----------------------------	---------------------------------

Standards

Standards	UNE-EN 61347-1/A1, UNE-EN 61347-2-12/A1, UNE-EN 60929, UNE-EN 61010-1, UNE-EN 61000-6-3/A1, UNE-EN 61000-6-2
-----------	--

Other digital relay outputs

Type	Control de doble nivel
Maximum current	5A
Maximum switching capacity	1250 VA - 150 W
Maximum open contact voltage	250Vca
Electrical life	1x10 ⁵ ciclos
Mechanical life	2x10 ⁷ cycles

Digital relay outputs

Type	Control ON/OFF
Maximum current	10A
Maximum open contact voltage	250 V ~
Electrical life	100x10 ³ ciclos
Mechanical life	10x10 ⁶ cycles



CIRLAMP NODO DN

Public lighting control system

Code: M63021.

Maximum switching capacity	2500 W (AC1)
----------------------------	--------------

Mechanical characteristics

Weight (kg)	0,28
-------------	------

Measurement accuracy

Phase current measurement	< 5% FS
Reactive power measurement (kvar)	< 5% F.S.
Active power measurement (kW)	< 5% F.S.