

# CIRLAMP nodo DALI



CIRLAMP nodo DALI, For managing the lights with electronic ballasts/drivers with DALI protocol (lamp power of up to 600 W),

Code: M63030.    DESCATALOGADO

## Specifications

### AC power supply

Installation category	CAT III 300 V
Consumption	2 W / 16 VA
Frequency	50 / 60 Hz
Nominal voltage	184 ... 276 Vca (Autoalimentado)

### Current measurement circuit

Installation category	CAT III 300 V
Phase current measuring range	0,1 ... 3 A
Minimum current measurement	0,08 A

### Voltage measurement circuit

Installation category	CAT III 300 V
Input impedance	600 MΩ
Voltage measuring range	184 ... 276 Vac

### Electrical characteristics

Insulation voltage, circuit	4 kV RMS 50 Hz durante 1 minuto
-----------------------------	---------------------------------

### Standards

Standards	UNE-EN 61347-1/A1, UNE-EN 61347-2-12/A1, UNE-EN 60929, UNE-EN 61010-1, UNE-EN 61000-6-3/A1, UNE-EN 61000-6-2
-----------	--

### Digital relay outputs

Maximum current	10A
Maximum open contact voltage	250 V ~
Electrical life	100x10 <sup>3</sup> ciclos
Mechanical life	10x10 <sup>6</sup> cycles
Maximum switching capacity	2500 W (AC1)

### Mechanical characteristics

Weight (kg)	0,225
-------------	-------

### Measurement accuracy

Phase current measurement	< 5% FS
Reactive power measurement (kvar)	< 5% F.S.
Active power measurement (kW)	< 5% F.S.



## CIRLAMP nodo DALI

---

Public lighting control system

Code: M63030.

---