



## TP-23 400 / 5A

TP-23 400 / 5A

Code: M70116. DESCATALOGADO

- > Transformer
- > Flat strip(mm): 20 x 30
- > Class 0,5 Power (VA): 2,5
- > Class 1 Power (VA): 6
- > Class 3 Power (VA): 10
- > Measurement Range (A): 400/5
- > Input current: 400/5 A

### Description

Open-core transformers that can measure current without having to interrupt the electric supply. In other words, the installation does not have to be dismantled in order to install them.

- Range: 100 to 5000 A
- Busbar dimensions: 20 x 30 mm to 80 x 160 mm
- The transformer certificate is attached.

### Application

Converting a high nominal current to a lower current so that it can be measured by the unit. They have a split core and can be installed with no need to interrupt the installation's power supply.



# TP-23 400 /5A

Split-core measurement current transformer

Code: M70116.

## Specifications

### Electrical characteristics

Safety factor (SF)	FS 10
Power	6 VA (Class 1)

### Mechanical characteristics

Size (mm) width x height x depth	110 x 89 x 58 (mm)
Weight (kg)	0,73

### Environmental characteristics

Thermal Class	Class B (+130 °C)
Working temperature	-5 ... 40 °C

### Specific technical characteristics of current sensors

Operating voltage	0,72 kV~ max.
-------------------	---------------

### Current measurement circuit

Primary current measurement	400 A
Dynamic current (Idyn)	2,5 Ith
Thermal short-circuit current (Ith)	60 In
Transformation ratio	... / 5 A

### Standards

Standards	IEC 44-1, UNE 21 088-1, UL 94, VDE 0414
-----------	---

For other configurations see table of additional features




TP-23 400 /5A

Split-core measurement current transformer

Code: M70116.

Dimensions



Dimensions (mm)	TP-58	TP-88	TP-812	TP-816
a	50	80	80	80
b	80	80	120	160
c	78	108	108	120
d	114	144	144	184
e	145	145	185	245
f	32	32	32	52
g	32	32	32	47
h	32	32	32	52
i	32	32	32	38