



## TP-812 2500 /5A

TP-812 2500 /5A, Split core current transformers

Code: M7014A. DESCATALOGADO

- > Flat strip(mm): 80 x 120
- > System: Single-phase
- > Class 0,5 Power (VA): 10
- > Class 1 Power (VA): 17
- > Class 3 Power (VA): 25
- > Measurement Range (A): 2500/5
- > Input current: 2500 A
- > Transformer type: Split core

### Description

Open-core transformers that can measure current without having to interrupt the electric supply. In other words, the installation does not have to be dismantled in order to install them.

- Range: 100 to 5000 A
- Busbar dimensions: 20 x 30 mm to 80 x 160 mm
- The transformer certificate is attached.

### Application

Converting a high nominal current to a lower current so that it can be measured by the unit. They have a split core and can be installed with no need to interrupt the installation's power supply.



# TP-812 2500 /5A

Split-core measurement current transformer

Code: M7014A.

## Specifications

### Electrical characteristics

|                    |                   |
|--------------------|-------------------|
| Safety factor (SF) | FS 10             |
| Power              | 10 VA (Class 0,5) |

### Mechanical characteristics

|                                  |                     |
|----------------------------------|---------------------|
| Size (mm) width x height x depth | 185 x 144 x 50 (mm) |
| Weight (kg)                      | 1,347               |

### Environmental characteristics

|                     |                   |
|---------------------|-------------------|
| Thermal Class       | Class B (+130 °C) |
| Working temperature | -5 ... 40 °C      |

### Specific technical characteristics of current sensors

|                   |               |
|-------------------|---------------|
| Operating voltage | 0,72 kV~ max. |
|-------------------|---------------|

### Current measurement circuit

|                                     |           |
|-------------------------------------|-----------|
| Primary current measurement         | 2500 A    |
| Dynamic current (Idyn)              | 2,5 Ith   |
| Thermal short-circuit current (Ith) | 60 In     |
| Transformation ratio                | ... / 5 A |

### Standards

|           |   |
|-----------|---|
| Standards | IEC 44-1, UNE 21 088-1, UL 94, VDE 0414 |
|-----------|---|

For other configurations see table of additional features



## TP-812 2500 /5A

Split-core measurement current transformer

Code: M7014A.

## Dimensions

