

## TP-816 5000 /5A

TP-816 5000 /5A, Split core current transformers

Code: M70157.

- > Flat strip(mm): 80 x 160
- > System: Single-phase
- > Class 0,5 Power (VA): 20
- > Class 1 Power (VA): 25
- > Class 3 Power (VA): 30
- > Measurement Range (A): 5000/5
- > Input current: 5000 A
- > Transformer type: Split core

### Specifications

#### Electrical characteristics

Safety factor (SF)	FS 10
Power	20 VA (Class 0,5)

#### Mechanical characteristics

Size (mm) width x height x depth	245 x 184 x 70 (mm)
Weight (kg)	4,4

#### Environmental characteristics

Thermal Class	Class B (+130 °C)
Working temperature	-5 ... 40 °C

#### Specific technical characteristics of current sensors

Operating voltage	0,72 kV~ max.
-------------------	---------------

#### Current measurement circuit

Primary current measurement	5000 A
Dynamic current (Idyn)	2,5 Ith
Thermal short-circuit current (Ith)	60 In
Transformation ratio	... / 5 A

#### Standards

Standards	IEC 44-1, UNE 21 088-1, UL 94, VDE 0414
-----------	---





## TP-816 5000 /5A

Split-core measurement current transformer

Code: M70157.

### Dimensions



mm	TP-23	TP-58	TP-88	TP-812	TP-816
a	20	50	80	80	80
b	30	80	80	120	160
c	51	78	108	108	120
d	89	114	144	144	184
e	110	145	145	185	245
f	34	32	32	32	52
g	47	32	32	32	47
h	40	32	32	32	52
i	32	32	32	32	38