



### TC5 40/5A

TC5 40/5A, Current transformers narrow section

Code: M70311. DESCATALOGADO

> Flat strip(mm): 20 x 10 |25 x 5 |15 x 5

> System: Single-phase> Class 3 Power (VA): 1,5> Measurement Range (A): 40/5

> Input current: 40 A

> Transformer type: Closed core

#### Description

o Type: bar entrance

 $\circ~$  Types: from 40 to 4000 A

o Internal diameter: from 20.3 to 63 mm, depending on the type

 $\circ~$  Busbar dimensions: from 25 x 5 mm to 30 x 100 mm

o Individual certificate available on request

o DIN rail fixing accessory (Types TC5 and TC6)

o Secondary coding types .../5 A (on demand .../1 A. **TC4** not available)

#### **Application**

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers.







## TC5 40/5A

Current transformers narrow section

Code: M70311.

### **Specifications**

Safety factor (SF)	FS 5
Power	VA (Class 1)
Mechanical characteristics	
Size (mm) width x height x depth	58 x 77 x 59 (mm)
Envelope	Plastic wrap V0 self-extinguishing, UL 94
Fastening	DIN rail with accessory
Weight (kg)	0,3
Environmental characteristics	
Thermal Class	Class B (+130 °C)
Protection class	IP 20
Relative humidity (without condensation)	15 95 %
Specific technical characteristics of current sensors	
Inner diameter Ø (mm)	20,3
Operating voltage	0,72 kV~ max.
Current measurement circuit	
Nominal frequency	50 / 60 Hz
Primary current measurement	40 A
Dynamic current (Idyn)	2,5 lth
Thermal short-circuit current (Ith)	60 ln
Transformation ratio	/ 5 A
Standards	
Standards	IEC 61869-1, IEC 61869-2, BS2627
Stallagins	120 010005 1, 120 010005 2, 852027

For other configurations see table of additional features









## TC5 40/5A

Current transformers narrow section

Code: M70311.

# **Dimensions**



