



### TC5.2 125/5A

TC5.2 125/5A, Current transformers narrow section

Code: M70322. DESCATALOGADO

> Flat strip(mm): 20 x 12 | 25 x 10 | 30 x 10

> System: Single-phase> Class 1 Power (VA): 1,5> Class 3 Power (VA): 2

> Measurement Range (A): 125/5

> Input current: 125 A

> Transformer type: Closed core

#### Description

- o Type: bar entrance
- $\circ$  Types: from 40 to 4000 A
- $\circ~$  Internal diameter: from 20.3 to 63 mm, depending on the type
- $\circ$  Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- o Individual certificate available on request
- o DIN rail fixing accessory (Types **TC5** and **TC6**)
- $\circ~$  Secondary coding types .../5 A (on demand .../1 A. TC4 not available)

#### **Application**

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers.







## TC5.2 125/5A

Current transformers narrow section

Code: M70322.

#### **Specifications**

Safety factor (SF)	FS 5
Power	1.5 VA (Class 1)
Mechanical characteristics	
Size (mm) width x height x depth	58 x 77 x 59 (mm)
Envelope	Plastic wrap V0 self-extinguishing, UL 94
Weight (kg)	0,171
Environmental characteristics	
Thermal Class	Class B (+130 °C)
Protection class	IP 20
Relative humidity (without condensation)	15 95 %
Specific technical characteristics of current sensors	
Inner diameter Ø (mm)	22
Operating voltage	0,72 kV~ max.
Current measurement circuit	
Nominal frequency	50 / 60 Hz
Primary current measurement	125 A
Primary current measurement  Dynamic current (Idyn)	125 A 2,5 lth
Dynamic current (Idyn)	2,5 lth
Dynamic current (Idyn)  Thermal short-circuit current (Ith)	2,5 lth 60 ln
Dynamic current (Idyn)  Thermal short-circuit current (Ith)  Transformation ratio	2,5 lth 60 ln

For other configurations see table of additional features









## TC5.2 125/5A

Current transformers narrow section

Code: M70322.

# **Dimensions**



