



## TC5.2 400/5A

TC5.2 400/5A, Current transformers narrow section

Code: M70327. (CONSULTAR DISPONIBILIDAD)

- > Flat strip(mm): 20 x 12 | 25 x 10 | 30 x 10
- > System: Single-phase
- > Class 0,5 Power (VA): 3,5
- > Class 1 Power (VA): 5
- > Class 3 Power (VA): 7,5
- > Measurement Range (A): 400/5
- > Input current: 400 A
- > Transformer type: Closed core

### Description

- Type: bar entrance
- Types: from 40 to 4000 A
- Internal diameter: from 20.3 to 63 mm, depending on the type
- Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- Individual certificate available on request
- DIN rail fixing accessory (Types **TC5** and **TC6**)
- Secondary coding types .../5 A (on demand .../1 A. **TC4** not available)

### Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers.



# TC5.2 400/5A

Current transformers narrow section

Code: M70327.

## Specifications

### Electrical characteristics

Safety factor (SF)	FS 5
Power	5 VA (Class 1)

### Mechanical characteristics

Size (mm) width x height x depth	58 x 77 x 59 (mm)
Envelope	Plastic wrap V0 self-extinguishing, UL 94
Weight (kg)	0,191

### Environmental characteristics

Thermal Class	Class B (+130 °C)
Protection class	IP 20
Relative humidity (without condensation)	15 ... 95 %

### Specific technical characteristics of current sensors

Inner diameter Ø (mm)	22
Operating voltage	0,72 kV~ max.

### Current measurement circuit

Nominal frequency	50 / 60 Hz
Primary current measurement	400 A
Dynamic current (Idyn)	2,5 Ith
Thermal short-circuit current (Ith)	60 In
Transformation ratio	... / 5 A

### Standards

Standards	IEC 61869-1, IEC 61869-2, BS2627
-----------	----------------------------------

For other configurations see table of additional features



## TC5.2 400/5A

Current transformers narrow section

Code: M70327.

## Dimensions

