



TC8 300/5A

TC8 300/5A

Code: M7036B. **DESCATALOGADO**

> Transformer

> Flat strip(mm): 50 x 30 |60 x 12 > Class 0,5 Power (VA): 2,5

> Class 1 Power (VA): 5

> Class 3 Power (VA): 7,5

> Measurement Range (A): 300/5

> Input current: 300 A

Description

- o Type: bar entrance
- \circ Types: from 40 to 4000 A
- $\circ~$ Internal diameter: from 20.3 to 63 mm, depending on the type
- \circ Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- o Individual certificate available on request
- o DIN rail fixing accessory (Types **TC5** and **TC6**)
- $\circ~$ Secondary coding types .../5 A (on demand .../1 A. TC4 not available)

Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers.







TC8 300/5A

Current transformers narrow section

Code: M7036B.

Specifications

FS 5			
5 VA (Class 1)			
84.5 x 109 x 78 (mm)			
Plastic wrap V0 self-extinguishing, UL 94			
0,51			
Class B (+130 °C)			
IP 20			
15 95 %			
44			
0,72 kV~ max.			
50 / 60 Hz			
300 A			
2,5 lth			
60 In			
/ 5 A			
/ 5 A			

For other configurations see table of additional features








TC8 300/5A

Current transformers narrow section

Code: M7036B.

Dimensions



	TC 5 TCH 5	TC 5.2 TCH 5.2	TC 6.2 TCH6.2	TC 6 TCH 6	TC 8 TCH 8	TC 10 TCH 10
а	58	58	64	64	84,5	108
b	70	70	80,5	80,5	102	130
с	29	29	34	34	46	61
d	20,3	22	26	28,5	44	63
е	45	45	60,5	66,5	69	
f	32	32	44	44	50	50
g	59	59	71	71,2	78	78
h	5,6	5,6	5,6	5,6	6,6	6,6
i	48	48	60	60	64	64
j	39	39	46	46	62	86
k	25,6	30,6	30,6	40,6	60,6	80,6
1	15,6	15,6	20,6	25,2	30,6	50,8

