

### TC12 1500/5A

TC12 1500/5A, Current transformers narrow section

#### Code: M70383. CONSULTAR DISPONIBILIDAD

- > Flat strip(mm): 100 x 50
- > System: Single-phase
- > Class 0,5 Power (VA): 15
- > Class 1 Power (VA): 20
- > Class 3 Power (VA): 30
- > Measurement Range (A): 1500/5
- > Input current: 1500 A
- > Transformer type: Closed core

#### Description

- Type: bar entrance
- $\circ$  Types: from 40 to 4000 A
- $\circ~$  Internal diameter: from 20.3 to 63 mm, depending on the type
- $\circ~$  Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- Individual certificate available on request
- $\circ~$  DIN rail fixing accessory (Types TC5 and TC6)
- Secondary coding types .../5 A (on demand .../1 A. TC4 not available)

#### Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers.

## Circutor



### TC12 1500/5A

Current transformers narrow section

Code: M70383.

#### Specifications

Electrical characteristics	
Safety factor (SF)	FS 5
Power	20 VA (Class 1)
Mechanical characteristics	
Size (mm) width x height x depth	129 x 155 x 78 (mm)
Envelope	Plastic wrap VO self-extinguishing, UL 94
Weight (kg)	0,711
Environmental characteristics	
Thermal Class	Class B (+130 °C)
Protection class	IP 20
Relative humidity (without condensation)	15 95 %
Specific technical characteristics of current sensors	
Operating voltage	0,72 kV~ max.
Current measurement circuit	
Nominal frequency	50 / 60 Hz
Primary current measurement	1500 A
Dynamic current (Idyn)	2,5 lth
Thermal short-circuit current (Ith)	60 In
Transformation ratio	/ 5 A
Standards	
Standards	IEC 61869-1, IEC 61869-2, BS2627

For other configurations see table of additional features





## TC12 1500/5A

Current transformers narrow section

Code: M70383.

# Dimensions

×

