



TC4 75/5A

TC4 75/5A, Current transformers narrow section

Code: M703D7.

> Flat strip(mm): 30 x 10 |20 x 10 |25 x 5

> System: Single-phase > Class 3 Power (VA): 1,25 > Measurement Range (A): 75/5

> Input current: 75 A

> Transformer type: Closed core

Description

- o Type: bar entrance
- O Types: from 40 to 4000 A
- $\circ~$ Internal diameter: from 20.3 to 63 mm, depending on the type
- \circ Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- Individual certificate available on request
- o DIN rail fixing accessory (Types TC5 and TC6)
- o Secondary coding types .../5 A (on demand .../1 A. **TC4** not available)

Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers.







TC4 75/5A

Current transformers narrow section

Code: M703D7.

Specifications

Safety factor (SF)	FS 5
Power	1.25 VA (Class 3)
Mechanical characteristics	
Size (mm) width x height x depth	50 x 77 x 56 (mm)
Envelope	Plastic wrap V0 self-extinguishing, UL 94
Weight (kg)	0,171
Environmental characteristics	
Thermal Class	Class B (+130 °C)
Protection class	IP 20
Relative humidity (without condensation)	15 95 %
Specific technical characteristics of current sensors	
Inner diameter Ø (mm)	21
Operating voltage	0,72 kV~ max.
Current measurement circuit	
Nominal frequency	50 / 60 Hz
Primary current measurement	75 A
Dynamic current (Idyn)	2,5 lth
Thermal short-circuit current (Ith)	60 ln
Transformation ratio	/ 5 A
Standards	
	IEC 61869-1, IEC 61869-2, BS2627
Standards	IEC 01003-1, IEC 01003-2, D32027

For other configurations see table of additional features









TC4 75/5A

Current transformers narrow section

Code: M703D7.

Dimensions



