



TCH6 400/5A

TCH6 400/5A, Current transformers high accuracy and narrow section

Code: M70435.

> Flat strip(mm): 30 x 15 |20 x 10 |40 x 10

> System: Single-phase > Class 0,2 Power (VA): 5 > Class 0,2S Power (VA): 1 > Class 0,5S Power (VA): 5

> Measurement Range (A): 400/5

> Input current: 400 A

> Transformer type: Closed core

Description

- o Type: bar entrance
- \circ Types: from 40 to 4000 A
- o Internal diameter: from 20.3 to 63 mm, depending on the type
- O Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- o Transformer certificate sheet is attached
- $\circ~$ Accessory on request for fixing on DIN rail (Types TCH6 and TCH6.2)
- o Secondary coding types .../5 A (on demand .../1 A.)

Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers and a high accuracy is required.







TCH6 400/5A

Current transformers narrow section and high accuracy

Code: M70435.

Specifications

| Safety factor (SF) | FS 5 | | | |
|---|---|--|--|--|
| Power | 5 VA (Class 0,2) | | | |
| rowei | 3 VA (Class 0,2) | | | |
| Mechanical characteristics | | | | |
| Size (mm) width x height x depth | 68 x 87.9 x 71.6 (mm) | | | |
| Envelope | Plastic wrap V0 self-extinguishing, UL 94 | | | |
| Weight (kg) | 0,289 | | | |
| Environmental characteristics | | | | |
| Thermal Class | Class B (+130 °C) | | | |
| Protection class | IP 20 | | | |
| Relative humidity (without condensation) | 15 95 % | | | |
| Specific technical characteristics of current sensors | | | | |
| Inner diameter Ø (mm) | 28,5 | | | |
| Operating voltage | 0,72 kV~ max. | | | |
| Current measurement circuit | | | | |
| Nominal frequency | 50 / 60 Hz | | | |
| Primary current measurement | 400 A | | | |
| Dynamic current (Idyn) | 2,5 lth | | | |
| Dynamic corrent (loyil) | | | | |
| Thermal short-circuit current (Ith) | 60 In | | | |
| | 60 In / 5 A | | | |
| Thermal short-circuit current (Ith) | | | | |

тсн

Current transformers narrow section and high accuracy

| CODE | TYPE | Measurement Range (A) | Flat strip(mm) | Class 0,2 Power (VA) | Class 0,2S Power (VA) | Class 0,5S Power (VA) |
|---------|---------------|-----------------------|----------------|-------------------------|--------------------------|--------------------------|
| TCH12 | | | | | | |
| M70486. | TCH12 2500/5A | 2500/5 | 100 x 50 | 20 | 15 | 20 |

For other configurations see table of additional features $% \left(1\right) =\left(1\right) \left(1\right) \left($







TCH6 400/5A

Current transformers narrow section and high accuracy

Code: M70435.

Dimensions



