

TCH6 500/5A

TCH6 500/5A, Current transformers high accuracy and narrow section

Code: M70436.

- > Flat strip(mm): 30 x 15 |20 x 10 |40 x 10
- > System: Single-phase
- > Class 0,2 Power (VA): 7,5
- > Class 0,2S Power (VA): 5
- > Class 0,5S Power (VA): 7,5
- > Measurement Range (A): 500/5
- > Input current: 500 A
- > Transformer type: Closed core

Description

- Type: bar entrance
- $\circ~$ Types: from 40 to 4000 A
- $\circ~$ Internal diameter: from 20.3 to 63 mm, depending on the type
- $\circ~$ Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- Transformer certificate sheet is attached
- $\circ~$ Accessory on request for fixing on DIN rail (Types TCH6 and TCH6.2)
- $\circ~$ Secondary coding types .../5 A (on demand .../1 A.)

Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers and a high accuracy is required.

Circutor



TCH6 500/5A

Current transformers narrow section and high accuracy

Code: M70436.

Specifications

Safety factor (SF)	FS 5				
Power	7.5 VA (Class 0,2)	7.5 VA (Class 0,2)			
Mechanical characteristics					
Size (mm) width x height x depth	69 x 87.1 x 71.7 (mm)				
Envelope	Plastic wrap VO self-extinguishing, UL 94				
Weight (kg)	0,3				
Environmental characteristics					
Thermal Class	Class B (+130 °C)				
Protection class	IP 20				
Relative humidity (without condensation)	15 95 %				
Specific technical characteristics of current sensors					
Inner diameter Ø (mm)	28,5				
Operating voltage	0,72 kV~ max.				
Current measurement circuit					
Nominal frequency	50 / 60 Hz				
Primary current measurement	500 A				
Dynamic current (Idyn)	2,5 lth				
	60 In				
Thermal short-circuit current (Ith)					
Thermal short-circuit current (Ith) Transformation ratio	/ 5 A				

тсн

Current transformers narrow section and high accuracy

CODE	TYPE	Measurement Range (A)	Flat strip(mm)	Class 0,2 Power (VA)	Class 0,2S Power (VA)	Class 0,5S Power (VA)
TCH12						
M70486.	TCH12 2500/5A	2500/5	100 x 50	20	15	20

For other configurations see table of additional features





TCH6 500/5A

Current transformers narrow section and high accuracy

Code: M70436.

Dimensions

×

