



## TCH6.2 60/5A

TCH6.2 60/5A, Current transformers high accuracy and narrow section

Code: M7044C. CONSULTAR DISPONIBILIDAD

> Flat strip(mm): 20 x 20 | 25 x 12 | 30 x 10

> System: Single-phase > Class 0,2 Power (VA): 0,5 > Measurement Range (A): 60/5

> Input current: 60 A

> Transformer type: Closed core

#### Description

- o Type: bar entrance
- O Types: from 40 to 4000 A
- o Internal diameter: from 20.3 to 63 mm, depending on the type
- $\circ$  Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- Transformer certificate sheet is attached
- Accessory on request for fixing on DIN rail (Types TCH6 and TCH6.2)
- $\circ~$  Secondary coding types .../5 A (on demand .../1 A.)

#### **Application**

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers and a high accuracy is required.







# TCH6.2 60/5A

Current transformers narrow section and high accuracy

Code: M7044C.

### **Specifications**

Safety factor (SF)	FS 5
Power	0.5 VA (Class 0,2)
Mechanical characteristics	
Size (mm) width x height x depth	75 x 87.16 x 71.13 (mm)
Envelope	Plastic wrap V0 self-extinguishing, UL 94
Weight (kg)	0,21
Environmental characteristics	
Thermal Class	Class B (+130 °C)
Protection class	IP 20
Relative humidity (without condensation)	15 95 %
Specific technical characteristics of current sensors	
Inner diameter Ø (mm)	26
Operating voltage	0,72 kV~ max.
Current measurement circuit	
Nominal frequency	50 / 60 Hz
Primary current measurement	60 A
Dynamic current (Idyn)	2,5 lth
Thermal short-circuit current (Ith)	60 ln
	/ 5 A
Transformation ratio	/ 3//
Transformation ratio  Standards	, 51,
	IEC 44-1, BS2627

For other configurations see table of additional features







# TCH6.2 60/5A

Current transformers narrow section and high accuracy


Code: M7044C.


### **Dimensions**


- 8

- 8 - 99

-02







**TCH 6.2** 

