



TCH8 600/5A

TCH8 600/5A, Current transformers high accuracy and narrow section

Code: M70463. CONSULTAR DISPONIBILIDAD

> Flat strip(mm): 50 x 30 |60 x 12

> System: Single-phase

> Class 0,2 Power (VA): 10

> Class 0,2S Power (VA): 5

> Class 0,5S Power (VA): 10

> Measurement Range (A): 600/5

> Input current: 600 A

> Transformer type: Closed core

Description

- o Type: bar entrance
- \circ Types: from 40 to 4000 A
- o Internal diameter: from 20.3 to 63 mm, depending on the type
- O Busbar dimensions: from 25 x 5 mm to 30 x 100 mm
- o Transformer certificate sheet is attached
- $\circ~$ Accessory on request for fixing on DIN rail (Types TCH6 and TCH6.2)
- o Secondary coding types .../5 A (on demand .../1 A.)

Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the electrical supply can be interrupted to install transformers and a high accuracy is required.







TCH8 600/5A

Current transformers narrow section and high accuracy

Code: M70463.

Specifications

Safety factor (SF)	FS 5			
Power	10 VA (Class 0,2)			
Mechanical characteristics				
Size (mm) width x height x depth	84.1 x 114 x 83 (mm)			
Envelope	Plastic wrap V0 self-extinguishing, UL 94			
Weight (kg)	0,57			
Environmental characteristics				
Thermal Class	Class B (+130 °C)			
Protection class	IP 20			
Relative humidity (without condensation)	15 95 %			
Specific technical characteristics of current sensors				
Inner diameter Ø (mm)	44			
Operating voltage	0,72 kV~ max.			
Current measurement circuit				
Nominal frequency	50 / 60 Hz			
Primary current measurement	600 A			
Dynamic current (Idyn)	2,5 lth			
Thermal short-circuit current (Ith)	60 In			
	/ 5 A			
Transformation ratio	/ 3 A			
Transformation ratio Standards	/ 3 A			

TCH

Current transformers narrow section and high accuracy

CODE	TYPE	Measurement Range (A)	Flat strip(mm)	Class 0,2 Power (VA)	Class 0,2S Power (VA)	Class 0,5S Power (VA)
TCH6.2						
M70444.	TCH6.2 200/5A	200/5	20 x 20 25 x 12 30 x 10	5	3,5	5

For other configurations see table of additional features $% \left(x_{1},x_{2}\right) =\left(x$







TCH8 600/5A

Current transformers narrow section and high accuracy

Code: M70463.

Dimensions



