

TM45 25/5A, Current transformers, winding primary, DIN rail

Code: M70605.

- > System: Single-phase
- > Class 0,5 Power (VA): 2,5
- > Class 1 Power (VA): 5
- > Class 3 Power (VA): 7
- > Measurement Range (A): 25/5
- > Input current: 25 A
- > Transformer type: Winding primary

Description

- $\circ~$ Types: from 1 to 40 A
- Wound primary
- Assembly on DIN rail

Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the nominal current is not too high or a transformer has to be installed on the DIN rail.

Circutor



Current transformers, busbar and winding primary

Code: M70605.

Specifications

Electrical characteristics	
Safety factor (SF)	FS < 5
Power	2.5 VA (Class 0,5)
Mechanical characteristics	
Size (mm) width x height x depth	52.5 x 85 x 70 (mm)
Envelope	Plastic wrap VO self-extinguishing
Fastening	DIN rail
Weight (kg)	0,299
Environmental characteristics	
Thermal Class	Class A (+105 °C)
Specific technical characteristics of current sensors	
Operating voltage	0,72 kV~ max.
Current measurement circuit	
Nominal frequency	50 / 60 Hz
	25.4
Primary current measurement	25 A
Primary current measurement Dynamic current (Idyn)	25 A 2,5 Ith
Dynamic current (Idyn)	2,5 lth
Dynamic current (Idyn) Thermal short-circuit current (Ith)	2,5 lth 60 ln

TM45

Current transformers, winding primary, DIN rail

CODE	ТҮРЕ	Measurement Range (A)	Class 0,5 Power (VA)	Class 1 Power (VA)	Class 3 Power (VA)
M70601.	TM45 5 /5A	5/5	2,5	5	7
M70602.	TM45 10 / 5A	10/5	2,5	5	7
M70603.	TM45 15 /5A	15/5	2,5	5	7
M70604.	TM45 20 /5A	20/5	2,5	5	7
M70605.	TM45 25/5A	25/5	2,5	5	7
M70606.	TM45 30 /5A	30/5	2,5	5	7
M70607.	TM45 40 /5A	40/5	2,5	5	7
M70608.	TM45 50 /5A	50/5	2,5	5	7

Circutor

Creation date: 31/08/2025 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons. It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



Current transformers, busbar and winding primary

Code: M70605.

CODE	ТҮРЕ	Measurement Range (A)	Class 0,5 Power (VA)	Class 1 Power (VA)	Class 3 Power (VA)
M70609.	TM45 1 / 5A	1/5	2,5	5	7

For other configurations see table of additional features

Circutor




Current transformers, busbar and winding primary

Code: M70605.

Dimensions

Connections



Circutor