



TM45 40 /5A, Current transformers, winding primary, DIN rail

Code: M70607.

- > System: Single-phase
- > Class 0,5 Power (VA): 2,5
- > Class 1 Power (VA): 5
- > Class 3 Power (VA): 7
- > Measurement Range (A): 40/5
- > Input current: 40 A
- > Transformer type: Winding primary

#### Description

- $\circ~$  Types: from 1 to 40 A
- Wound primary
- O Assembly on DIN rail

### **Application**

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the nominal current is not too high or a transformer has to be installed on the DIN rail.







Current transformers, busbar and winding primary

Code: M70607.

### **Specifications**

Electrical characteristics	
	FS < 5
Safety factor (SF)  Power	2.5 VA (Class 0,5)
Power	Z.5 VA (CldSS U,5)
Mechanical characteristics	
Size (mm) width x height x depth	52.5 x 85 x 70 (mm)
Envelope	Plastic wrap V0 self-extinguishing
Fastening	DIN rail
Weight (kg)	0,289
Environmental characteristics	
Thermal Class	Class A (+105 °C)
Specific technical characteristics of current sensors	
Operating voltage	0,72 kV~ max.
Current measurement circuit	
Nominal frequency	50 / 60 Hz
Primary current measurement	40 A
Dynamic current (Idyn)	2,5 lth
Thermal short-circuit current (Ith)	60 In
Transformation ratio	/ 5 A
Standards	
Standards	IEC 44-1, UNE 21 088-1, UL 94, VDE 0414

#### TM45 Current transformers, winding primary, DIN rail

	Measurement Range (A)	Class 0,5 Power (VA)	class i Power (VA)	Class 3 Power (VA)
TM45 5 /5A	5/5	2,5	5	7
TM45 10 /5A	10/5	2,5	5	7
TM45 15 /5A	15/5	2,5	5	7
TM45 20 /5A	20/5	2,5	5	7
TM45 25/5A	25/5	2,5	5	7
TM45 30 /5A	30/5	2,5	5	7
TM45 40 /5A	40/5	2,5	5	7
TM45 50 /5A	50/5	2,5	5	7
	TM45 10 /5A  TM45 15 /5A  TM45 20 /5A  TM45 25/5A  TM45 30 /5A  TM45 40 /5A	TM45 10 /5A 10/5  TM45 15 /5A 15/5  TM45 20 /5A 20/5  TM45 25/5A 25/5  TM45 30 /5A 30/5  TM45 40 /5A 40/5	TM45 10 /5A 10/5 2,5  TM45 15 /5A 15/5 2,5  TM45 20 /5A 20/5 2,5  TM45 25/5A 25/5 2,5  TM45 30 /5A 30/5 2,5  TM45 40 /5A 40/5 2,5	TM45 10 /5A       10/5       2,5       5         TM45 15 /5A       15/5       2,5       5         TM45 20 /5A       20/5       2,5       5         TM45 25/5A       25/5       2,5       5         TM45 30 /5A       30/5       2,5       5         TM45 40 /5A       40/5       2,5       5







Current transformers, busbar and winding primary

Code: M70607.

CODE	TYPE	Measurement Range (A)	Class 0,5 Power (VA)	Class 1 Power (VA)	Class 3 Power (VA)
M70609.	TM45 1 /5A	1/5	2,5	5	7

For other configurations see table of additional features







Current transformers, busbar and winding primary

Code: M70607.

**Dimensions** Connections



