



TM45 50 /5A, Current transformers, winding primary, DIN rail

Code: M70608.

> System: Single-phase

> Class 0,5 Power (VA): 2,5

> Class 1 Power (VA): 5

> Class 3 Power (VA): 7

> Measurement Range (A): 50/5

> Input current: 50 A

> Transformer type: Winding primary

Description

- $\circ~$ Types: from 1 to 40 A
- Wound primary
- o Assembly on DIN rail

Application

Converting a high nominal current to a lower current so that it can be measured by the unit. In installations where the nominal current is not too high or a transformer has to be installed on the DIN rail.







Current transformers, busbar and winding primary

Code: M70608.

Specifications

FS < 5		
n)		
Plastic wrap V0 self-extinguishing		
DIN rail		
0,28		
50 / 60 Hz		
60 In		
88-1, UL 94, VDE 0414		
)		

TM45 Current transformers, winding primary, DIN rail

	Measurement Range (A)	Class 0,5 Power (VA)	class i Power (VA)	Class 3 Power (VA)
TM45 5 /5A	5/5	2,5	5	7
TM45 10 /5A	10/5	2,5	5	7
TM45 15 /5A	15/5	2,5	5	7
TM45 20 /5A	20/5	2,5	5	7
TM45 25/5A	25/5	2,5	5	7
TM45 30 /5A	30/5	2,5	5	7
TM45 40 /5A	40/5	2,5	5	7
TM45 50 /5A	50/5	2,5	5	7
	TM45 10 /5A TM45 15 /5A TM45 20 /5A TM45 25/5A TM45 30 /5A TM45 40 /5A	TM45 10 /5A 10/5 TM45 15 /5A 15/5 TM45 20 /5A 20/5 TM45 25/5A 25/5 TM45 30 /5A 30/5 TM45 40 /5A 40/5	TM45 10 /5A 10/5 2,5 TM45 15 /5A 15/5 2,5 TM45 20 /5A 20/5 2,5 TM45 25/5A 25/5 2,5 TM45 30 /5A 30/5 2,5 TM45 40 /5A 40/5 2,5	TM45 10 /5A 10/5 2,5 5 TM45 15 /5A 15/5 2,5 5 TM45 20 /5A 20/5 2,5 5 TM45 25/5A 25/5 2,5 5 TM45 30 /5A 30/5 2,5 5 TM45 40 /5A 40/5 2,5 5







Current transformers, busbar and winding primary

Code: M70608.

CODE	TYPE	Measurement Range (A)	Class 0,5 Power (VA)	Class 1 Power (VA)	Class 3 Power (VA)
M70609.	TM45 1 /5A	1/5	2,5	5	7

For other configurations see table of additional features







Current transformers, busbar and winding primary

Code: M70608.

Dimensions

Connections





