



TI-420-105-1000A, Current transformer with converter 4 ... 20 mA

Code: M70834.

> Inner diameter (mm): 105 > Analog output: 4...20 mA > Measurement Range (A): 1000 > Input current: 1000 A

> Transformer type: Current transformer with 4 ... 20 mA converter

Description

- \circ $\,$ Needs an output power supply of 10 ... 28 V dc
- Primary current: from 2.5 to 1500 A ~, depending on the type
- o Secondary current: 4 ... 20 mA
- o Internal diameter: from 35 to 105 mm, depending on the type
- $\circ~$ Busbar dimensions: from 35 to 105 mm, depending on the type

Application

Used in power lines to obtain a current proportional to the primary current rated at 4 ... 20 mA in the secondary







Current transformers with converter

Code: M70834.

Specifications

10 28 Vdc
170 x 146 x 33 (mm)
0,6
-10°+50 °C
105
0,72 kV~ max.
50 / 60 Hz
1000 A
1,5 ln
4 20 mA
IEC 44-1, UNE 21 088-1, IEC 664, VDE0110, VDE0414, UL 94, IEC 1010-1, EN 61010-
±1,5% In

Current transformer with converter 4 ... 20 mA

CODE	TYPE	Measurement Range (A)	Inner diameter (mm)
1028 Vdc supply, C	Output 420 mA		
M70811.	TI-420-35-2.5A	2.5	35
M70812.	TI-420-35-5A	5	35
M70813.	TI-420-35-10A	10	35
M70814.	TI-420-35-20A	20	35
M70815.	TI-420-35-50A	50	35
M70816.	TI-420-35-100A	100	35
M70817.	TI-420-35-250A	250	35







Current transformers with converter

Code: M70834.

CODE	ТҮРЕ	Measurement Range (A)	Inner diameter (mm)	
M70821.	TI-420-70-100A	100	70	
M70822.	TI-420-70-250A	250	70	
M70823.	TI-420-70-500A	500	70	
M70824.	TI-420-70-750A	750	70	
M70831.	TI-420-105-250A	250	105	
M70832.	TI-420-105-500A	500	105	
M70833.	TI-420-105-750A	750	105	
M70834.	TI-420-105-1000A	1000	105	
M70835.	TI-420-105-1500A	1500	105	

For greater currents, use: transformer + transducer







Current transformers with converter

Code: M70834.

Dimensions

Connections





