



TC5 420 5A

TC5 420 5A, Current transformers narrow section

Code: M72112.

- > Flat strip(mm): 25 x 5
- > Inner diameter (mm): 20
- > Analog output: 4...20 mA
- > Measurement Range (A): 5
- > Input current: 5 A
- > Transformer type: Current transformer with 4 ... 20 mA converter

Description

- Needs an output power supply of 7.5 ... 36 Vdc
- Primary current: from 5 to 300 Aac, depending on the type
- Secondary current: 4 ... 20 mA
- Internal diameter: from 20 to 44 mm, depending on the type
- Busbar dimensions: from 25 x 5 mm to 60 x 12 mm

Application

Used in power lines to obtain a current proportional to the primary current rated at 0..20 mA / 4...20 mA in the secondary



TC5 420 5A

Current transformer with converter

Code: M72112.

Specifications

Auxiliary power supply

| | |
|---------|----------------|
| Voltage | 7,5 ... 36 Vdc |
|---------|----------------|

Electrical characteristics

| | |
|--------------------|--------|
| Safety factor (SF) | FS < 5 |
|--------------------|--------|

Mechanical characteristics

| | |
|----------------------------------|------------------------------------|
| Size (mm) width x height x depth | 58 x 70 x 32 (mm) |
| Envelope | Plastic wrap V0 self-extinguishing |
| Weight (kg) | 0,301 |

Environmental characteristics

| | |
|---------------|-------------------|
| Thermal Class | Class B (+130 °C) |
|---------------|-------------------|

Specific technical characteristics of current sensors

| | |
|-----------------------|---------------|
| Inner diameter Ø (mm) | 20 |
| Operating voltage | 0,72 kV~ max. |

Current measurement circuit

| | |
|-------------------------------------|-------------|
| Nominal frequency | 50 / 60 Hz |
| Primary current measurement | 100 A |
| Dynamic current (Idyn) | 2,5 Ith |
| Thermal short-circuit current (Ith) | 60 In |
| Transformation ratio | 4 ... 20 mA |

TC-420

Current transformers with converter 4 ... 20 mA or 0 ... 20 mA

| CODE | TYPE | Measurement Range (A) | Flat strip(mm) | Inner diameter (mm) |
|---|---------------|-----------------------|----------------|---------------------|
| Output 4...20 mA, ext. supply 7,5...36 Vdc | | | | |
| M72112. | TC5 420 5A | 5 | 25 x 5 | 20 |
| M72113. | TC5 420 10A | 10 | 25 x 5 | 20 |
| M72114. | TC5 420 20A | 20 | 25 x 5 | 20 |
| M72132. | TC6 420 100A | 100 | 40 x 10 | 28 |
| M72134. | TC6 420 200A | 200 | 40 x 10 | 28 |
| M72136. | TC6 420 300A | 300 | 40 x 10 | 28 |
| M72131. | TC6 420 50A | 50 | 40 x 10 | 28 |
| M72152. | TC8 420 1000A | 1000 | 60 x 12 | 44 |



TC5 420 5A

Current transformer with converter

Code: M72112.

| CODE | TYPE | Measurement Range (A) | Flat strip(mm) | Inner diameter (mm) |
|---------|---------------|-----------------------|----------------|---------------------|
| M72153. | TC8 420 1500A | 1500 | 60 x 12 | 44 |
| M72151. | TC8 420 500A | 500 | 60 x 12 | 44 |

For greater currents, use: transformer + transducer



TC5 420 5A

Current transformer with converter

Code: M72112.

Dimensions

