MC3 - 250 A

MC3 - 250 A, Three-phase current transformers

Code: M73123.

> Inner diameter (mm): 26
> System: Three-phase
> Class 0,5 Power (VA): 0,1
> Max. Current (A): 250
> Transformer type: Closed core

Description

Current transformers specifically designed to be installed above a switch:

○ Transformer range from 63 to 250 A

○ Secondary 250 mA

○ Compatible with **CIRCUTOR**'s **MC** range of products: **CVM-MINI, CVM-NET, CVM-NET4, CVM-C, CVM-B, CDP-0, CDP-G**

Application

Installation in confined spaces, utilizing the space above the circuit breakers and earth leakage protection In installations that allow the power supply to be shut down for the installation of transformers.

Circutor

Creation date: 01/06/2025 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.

Page 1 of 4

MC3 - 250 A

Three-phase efficient current transformers

Code: M73123.

Specifications

Electrical characteristics

Safety factor (SF)	FS 5
Power	0.1 VA (Class 0,5)
Insulation voltage between terminals S1-S2	3 kV

Mechanical characteristics

Size (mm) width x height x depth	120.7 x 24 x 59.2 (mm)
Envelope	Plastic V0 self-extinguishing
Weight (kg)	0,218

Environmental characteristics

Thermal Class	Class B (+130 ºC)
Protection class	IP 20

Specific technical characteristics of current sensors

Inner diameter Ø (mm)	26
Operating voltage	0,72 kV~ máx.

Current measurement circuit

Nominal frequency	50 / 60 Hz
Primary current measurement	250 A
Dynamic current (Idyn)	2,5 Ith
Thermal short-circuit current (Ith)	60 In
Transformation ratio	.../ 250 mA

Standards

Standards	IEC 60044-1

Measurement accuracy

Accuracy	Clase 0,5

MC3
Three-phase current transformers

CODE	TYPE	Measurement Range (A)	Inner diameter (mm)	Class 0,5 Power (VA)
M73121.	MC3 - 63 A	63	7,1	0,1
M73122.	MC3 - 125 A	125	14,6	0,1
M73123.	MC3 - 250 A	250	26	0,1

MC3 - 250 A

Three-phase efficient current transformers

Code: M73123.

The MC/SC3 transformers with a 250 mA output are only compatible with network analysers type MC

MC3 – 250 A

Three-phase efficient current transformers

Code: M73123.

Dimensions

Connections