



## STP-24 150/5A

STP-24 150/5A, Split core current transformer

Code: M73325.

- > Inner diameter (mm): 24
- > System: Single-phase
- > Class 3 Power (VA): 1
- > Measurement Range (A): 150/5
- > Input current: 150 A
- > Power (VA): 1
- > Transformer type: Split core

### Specifications

#### Electrical characteristics

Safety factor (SF)	2.5
Power	1 VA (Class 3)
Insulation voltage between terminals S1-S2	3 kV 1 min

#### Mechanical characteristics

Size (mm) width x height x depth	66 x 76 x 55 (mm)
Envelope	Plastic V0 self-extinguishing (UNE 21031)
Weight (kg)	0,17

#### Environmental characteristics

Thermal Class	class B (+130 °C)
Relative humidity (without condensation)	15 ... 85%
Storage temperature	-40 ... +85 °C
Working temperature	-20 ... +55 °C

#### Specific technical characteristics of current sensors

Inner diameter Ø (mm)	24
Operating voltage	0,72 kV~ máx.

#### Current measurement circuit

Nominal frequency	50 / 60 Hz
Primary current measurement	150 A
Allowable overload	1,2 x I <sub>n</sub>
Dynamic current (I <sub>dyn</sub> )	2,5 I <sub>th</sub>
Thermal short-circuit current (I <sub>th</sub> )	60 I <sub>n</sub>
Minimum current measurement	0,01 x I <sub>n</sub>
Transformation ratio	... / 5A

#### Standards

Standards	IEC 60044-1, IEC 61010-1
-----------	--------------------------



## STP-24 150/5A

---

Split-core current Transformers

Code: M73325.

### Measurement accuracy

---

Accuracy

Clase 3

---



## STP-24 150/5A

Split-core current Transformers

Code: M73325.

### Dimensions

