



## STP-24 250/250 mA

STP-24 250/250 mA, Split core current transformer

Code: M7332700G0000

- > Inner diameter (mm): 24
- > System: Single-phase
- > Class 1 Power (VA): 0,1
- > Measurement Range (A): 250/250 mA
- > Input current: 250 A
- > Power (VA): 0.1
- > Transformer type: Split core

### Specifications

#### Electrical characteristics

Safety factor (SF)	2.5
Power	0.1 VA (Class 1)
Insulation voltage between terminals S1-S2	3 kV 1 min

#### Mechanical characteristics

Size (mm) width x height x depth	66 x 76 x 55 (mm)
Envelope	Plastic V0 self-extinguishing (UNE 21031)
Weight (kg)	0,26

#### Environmental characteristics

Thermal Class	class B (+130 °C)
Relative humidity (without condensation)	15 ... 85%
Storage temperature	-40 ... +85 °C
Working temperature	-20 ... +55 °C

#### Specific technical characteristics of current sensors

Inner diameter Ø (mm)	24
Operating voltage	0,72 kV~ máx.

#### Current measurement circuit

Nominal frequency	50 / 60 Hz
Primary current measurement	250 A
Allowable overload	1,2 x In
Dynamic current (Idyn)	2,5 Ith
Thermal short-circuit current (Ith)	60 In
Minimum current measurement	0,01 x In
Transformation ratio	... / 250 mA

#### Standards

Standards	IEC 60044-1, IEC 61010-1
-----------	--------------------------



## STP-24 250/250 mA

---

Split-core current Transformers

Code: M7332700G0000

### Measurement accuracy

---

Accuracy

Clase 1/3

---



## STP-24 250/250 mA

Split-core current Transformers

Code: M7332700G0000

### Dimensions

