

Kit4-CPRG-500



Kit4-CPRG-500, Clamp

Code: M810D3. **CONSULTAR DISPONIBILIDAD**

- > Nr Sensors: 4
- > Useful diam.(mm): 52
- > Measurement Range (A): 1 ... 500 A
- > I min.(A): 1

Description

CIRCUTOR offers a wide range of current sensors for its portable power analyzers. The products included in this range can be used to measure current levels from a few mA to up to several thousand amperes. In addition, the models are available in flexible and rigid format, offering the best solution for each installation.

Application

Measurement of energy values via portable power analyzers.



Kit4-CPRG-500

Current sensors for portable power analyzers

Code: M810D3.

Specifications

Mechanical characteristics

Size (mm) width x height x depth	45 x 216 x 111 (mm)
Weight (kg)	3

Specific technical characteristics of current sensors

Measurement range	1...500 Ac.a.
Dielectric rigidity	5200 V, 50 Hz, 1 min.
Output voltage	2 Vc.a.

Current measurement circuit

Nominal frequency	48...65 Hz
Tolerance	1...5A (3%) Fase: NC / 5...50A (0,7%) Fase: NC / 50...500A (0,7%) Fase: 1 °

CPG Clamps

CODE	TYPE	Measurement Range (A)	I min.(A)	Useful diam.(mm)	Flat strip(mm)
M810B1.	CPG-5	0,05 ... 5 A	0.05	20	20 x 5
M810B2.	CPG-100	1 ... 100 A	1	20	20 x 5
M810B3.	CPRG-500	1 ... 500 A	1	52	1 - 50 x 5 4 - 30 x 5
M810B4.	CPRG-1000	1 ... 1000 A	1	52	1 - 50 x 5 4 - 30 x 5
M810B5.	CPG-2000/200	1 ... 200 A / 10 ... 2000 A	1 10	64	5 - 125 x 5 3 -100 x 10
M810BD.	CFG-5	0,01 ... 5 A	0.01	52	1 - 50 x 5 4 - 30 x 5
M810BE.	CFG-10	0,005 ... 10 A	0.05	100	5 - 80 x 5 3 -80 x 10



Kit4-CPRG-500

Current sensors for portable power analyzers

Code: M810D3.

Dimensions

