



Kit3 CFLEX-120

Kit3CFLEX-120

Code: M81143. (CONSULTAR DISPONIBILIDAD)

- > AR5L
- > Clamp
- > Length: 120 cm
- > Nr Sensors: 3
- > Measurement Range (A): 20 ... 200 / 200...2000 / 2000 ... 20000 A
- > I Δ n min.(A): 1000
- > I min: 2/20/1000

Specifications

Environmental characteristics

| | |
|--|----------------|
| Relative humidity (without condensation) | 90% (a 50 °C) |
| Working temperature | -10 ... +55 °C |

Specific technical characteristics of current sensors

| | |
|------------------------------|------------------------------|
| Bandwidth | 10...20 KHZ |
| Measurement range | 5 A ... 20 kA |
| Allowable overvoltage output | 600 V (factor de cresta 1,5) |

Standards

| | |
|--|-------------------------|
| Electrical safety, Installation category | CAT III 100V, IEC 61010 |
| Electrical safety, Contamination level/class | Pollution resistance 2 |

Electrical safety

| | |
|------------|---|
| Insulation | Double-insulated electric shock protection class II (IEC 61010-1) |
|------------|---|

Mechanical characteristics

| | |
|-------------|-----|
| Weight (kg) | 1,2 |
|-------------|-----|

Measurement accuracy

| | |
|---------------------------|----|
| Phase current measurement | 1% |
|---------------------------|----|