



KIT 1-FLEX-R120

KIT 1-FLEX-R120, Flexible clamp

Code: M81613.

- > Length: 120 cm
- > Nr Sensors: 1
- > Usefull diam.(mm): 380
- > Measurement Range (A): 10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A
- > $I_{\Delta n}$ min.(A): 1
- > I min: 1 | 10 | 500

Description

The flexible current sensor can take alternating current measurements from any installation with a full rejection of DC components, a very low consumption of power, with no saturation problems, a low temperature dependence and a very good linearity. The flexible sensor has been designed according to the Rogowsky coil principle, measuring alternating current irrespective of the position of the conductor. The current conductor must not be near the coil cable joint, since the degree of error increases in this area. Its centred location also reduces the impact of external magnetic fields. Thanks to the flexibility of the current sensor, one or more conductors can be surrounded, regardless of their shape, to perform current measurement actions.

Application

These flexible current sensors have been specially designed for the **MYeBOX-150** and **MYeBOX-1500** portable power analysers.



KIT 1-FLEX-R120

Flexible Clamps

Code: M81613.

Specifications

Environmental characteristics

Protection class	IP 20 / IP 54 with terminal cover (optional) (for models Ø 85, 100, 116 mm)
Relative humidity (without condensation)	15...85 %
Storage temperature	-40...85 °C
Working temperature	-20...85 °C

Mechanical characteristics

Envelope	sensor material: Self-extinguishing UNE 21031 90 °C / Material couplings: PA V-0
----------	--

Specific technical characteristics of current sensors

External fields	± 2 %
Maximum temperature coefficient	± 0,05 %
Accuracy	± 1 %
Linearity	(10...100%) ± 0,2 %
Position sensitivity (cable connection)	± 3 %
Output voltage	76 µV/A a 50 Hz

Current measurement circuit

Nominal frequency	50Hz/60 Hz.
-------------------	-------------

Standards

Electrical safety, Installation category	1000V CAT III / 600V CAT IV
Electrical safety, Contamination level/class	Pollution resistance 2
Standards	Dielectric strength IEC 61010-2-32 (5,4 kV 50 Hz)

Electrical safety

Insulation	Double-insulated electric shock protection class II (IEC 61010-1)
------------	---

FLEX-R

Flexible sensors for MYeBOX analysers

CODE	TYPE	Measurement Range (A)	Nr Sensors
Flexible Clamps			
M81611.	KIT 1 -FLEX-R45	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	1
M81631.	KIT 3 -FLEX-R45	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	3
M81641.	KIT 4 -FLEX-R45	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	4
M81612.	KIT 1-FLEX-R80	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	1
M81632.	KIT 3-FLEX-R80	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	3



KIT 1-FLEX-R120

Flexible Clamps

Code: M81613.

CODE	TYPE	Measurement Range (A)	Nr Sensors
M81642.	KIT 4-FLEX-R80	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	4
M81613.	KIT 1-FLEX-R120	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	1
M81633.	KIT 3-FLEX-R120	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	3
M81643.	KIT 4-FLEX-R120	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	4

Includes 3 clamps (kit-3), amplifier and 9 V power supply