

kit 1 FLEX RMG120



kit 1 FLEX RMG120, Flexible Clamp

Code: M81912.

- > Length: 38 cm
- > Nr Sensors: 1
- > Usefull diam.(mm): 120
- > Measurement Range (A): 10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A
- > I min: 1 | 10 | 500

Description

The flexible current sensor can take alternating current measurements from any installation with a full rejection of DC components, a very low consumption of power, with no saturation problems, a low temperature dependence and a very good linearity. The flexible sensor has been designed according to the Rogowsky coil principle, measuring alternating current irrespective of the position of the conductor. The current conductor must not be near the coil cable joint, since the degree of error increases in this area. Its centred location also reduces the impact of external magnetic fields. Thanks to the flexibility of the current sensor, one or more conductors can be surrounded, regardless of their shape, to perform current measurement actions.

Application

These flexible current sensors have been specially designed for the **MYeBOX-150** and **MYeBOX-1500** portable power analysers.

kit 1 FLEX RMG120



Flexible Clamps

Code: M81912.

Specifications

Environmental characteristics

Protection class	IP 54
Relative humidity (without condensation)	15...85 %
Storage temperature	-40...85 °C
Working temperature	-20...85 °C

Mechanical characteristics

Envelope	Sensor material: Self-extinguishing UNE 21031 90 °C / Material couplings: PA V-0
----------	--

Specific technical characteristics of current sensors

External fields	± 2 %
Maximum temperature coefficient	± 0,05 %
Linearity	(10...100%) ± 0,2 %
Position sensitivity (cable connection)	± 3 %
Output voltage	100 µV/A a 50 Hz

Current measurement circuit

Nominal frequency	50Hz/60 Hz.
-------------------	-------------

Electrical safety

Insulation	Double-insulated electric shock protection class II (IEC 61010-1)
------------	---

Standards

Electrical safety, Contamination level/class	Pollution resistance 2
Standards	Dielectric strength IEC 61010-2-32 (5,4 kV 50 Hz), IEC 61010-1

FLEX-RMG

Flexible sensors for MYeBOX analysers

CODE	TYPE	Measurement Range (A)	Nr Sensors
M81911.	kit 1 FLEX RMG70	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	1
M81912.	kit 1 FLEX RMG120	10 ... 100 A / 100 ... 1000 A / 1000 ... 10000 A	1