



CIRE3/3 CP-100

CIRE3/3 CP-100

Code: M85030. **(CONSULTAR DISPONIBILIDAD)**

> Analyzer

Specifications

AC power supply

Installation category	CAT III 300 Vac (IEC 61010)
Consumption	9 VA
Frequency	50...60 Hz.
Nominal voltage	100...400 Vc.a.
Minimum current	0,01 x In

DC power supply

Nominal voltage	70...315 Vdc
-----------------	--------------

Environmental characteristics

Protection class	IP 53
Relative humidity (without condensation)	95%
Storage temperature	-10...+65 °C
Working temperature	10...+50 °C

Standards

Certifications	UL, VDE
Electrical safety, Maximum height (m)	2000
Standards	IEC 60664-1, IEC 61010-1, IEC 62053-21, UL94, VDE 0110, IEC 61000-3-2, IEC 61000-3-3, IEC 61000-6-4 , EN 55011 , EN 55022 , IEC 61000-6-2 , IEC 61000-4-2 , IEC 61000-4-3 , IEC 61000-4-4 , IEC 61000-4-5 , IEC 61000-4-8 , IEC 61000-6-1 , IEC 61000-4-11 ,UNE-ENV 50141

Current measurement circuit

Phase current measuring range	(.../2V) 2,5...100% Full scale clamp
Measurement units	Automatic scale change
Transformation ratio	Transformer

Voltage measurement circuit

Sampling frequency	45...65 Hz
Frequency measuring range	45...65 Hz

Mechanical characteristics

Weight (kg)	2,9
-------------	-----

Measurement accuracy

Phase current measurement	0.5% (see current clamp measurement error)
Active energy measurement (kWh)	1% (see measurement error of the current clamps)



CIRE3/3 CP-100

Code: M85030.

Active power measurement (kW)

1% (see measurement error of the current clamps)

Phase voltage measurement

0,5%