



KIT3 CPG-2000/200

KIT3 CPG-2000/200, Clamps

Code: M86018. DESCATALOGADO

- > Nr Sensors: 3 x CPG 2000/200 CIR-e+
- > Usefull diam.(mm): 64
- > Measurement Range (A): 10 ... 200 A / 150 ... 2000 A
- > I Δ n min.(A): 1
- > I min: 1 / 10

Specifications

Specific technical characteristics of current sensors

Full scale error	Escala 200: 0,5 % (+70 mA) / Escala 2000:0,5 % (+100 mA)
Measurement range	1...200 Ac.a. / 10...2000 Ac.a.
Dielectric rigidity	5200 V, 50 Hz, 1 min.
Output voltage	2 Vc.a.

Current measurement circuit

Nominal frequency	48...65 Hz
Tolerance	Escala de 200: 1...3A (0,5% + 70mV) Fase: NC / 3...10A (0,5% + 70mV) Fase: NC / 10...50 A (0,5% + 70mV) Fase: 1,5 ° / 50...200A (0,5% + 70mA) Fase: 1/ Escala de 2000: 10...150A (0,5% + 250mA) Fase: NC / 150...2000A (0,5% + 100mA) Fase: 0,5 °

Mechanical characteristics

Weight (kg)	4
-------------	---