

WGC-25, Residual current transformer

Code: P10151.

> Usefull diam.(mm): 25

> Cable (m): 0

> Max. Current (A): 63

#### Description

This new range features a series of improvements intended in particular for installing units on switchboards. Along with the usual attachment elements, this unit can be installed on DIN rails using an accessory, which facilitates its installation.

The residual current transformers of the **WGC** series offer better immunity to the transient current spikes that usually trigger the residual current protection. The residual current transformers of the **WGC** series have been designed to operate with the relays of the **WGC** series. The sensitivity (trip current) of the transformer-relay assembly is established by the associated relay.

## Circutor



Residual current transformers

Code: P10151.

#### Specifications

Pulse test (kV)	3 kV	3 kV	
Mechanical characteristics			
Size (mm) width x height x depth	60.5 x 64 x 50 (mm)		
Envelope	Self-extinguishing polycarbonate UL 94 VO	Self-extinguishing polycarbonate UL 94 V0	
Fastening	DIN rail with accessory (see code)	DIN rail with accessory (see code)	
Connection type	Screw terminal (Pz type)	Screw terminal (Pz type)	
Weight (kg)	0,08		
Environmental characteristics			
Protection class	IP 20 (Terminals) IEC 60529		
Relative humidity (without condensation)	5 95 %	5 95 %	
Working temperature	-20 + 70 °C		
Current measurement circuit			
Dynamic current (Idyn)	2,5 lth		
Permanent thermal current (Icth)	60 A		
Thermal short-circuit current (Ith)	1,8 kA / 1s		
Transformation ratio	30 / 0,06 A		
Maximum operating voltage (Um)	720 V		
Standards			
Electrical safety, Maximum height (m)	2000	2000	
	CAT III		
Electrical safety, Installation category	CATIN		
Electrical safety, Installation category Standards	IEC 60664-1, IEC 60664-3, IEC 60044-1		

#### WGC

Residual current transformer

CODE	ТҮРЕ	Inner diameter (mm)	Cable (m)	In (A)
P10181.	WGC-20-SC	20	0.5	63
P10182.	WGC-30-SC	30	0.5	63
P10131.	WGS-20	20	-	63
P10132.	WGS-30	30	-	63

## Circutor

Creation date: 17/07/2025 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons. It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



Residual current transformers

Code: P10151.

CODE	ТҮРЕ	Inner diameter (mm)	Cable (m)	In (A)
P10151.	WGC-25	25	-	63
P10152.	WGC-35	35	-	80
P10153.	WGC-55	55	-	160
P10154.	WGC-80	80	-	250
P10155.	WGC-110	115	-	400
P10156.	WGC-140	140	-	600
P10157.	WGC-180	180	-	800
P10158.	WGC-220x105	220 x 105	-	1250
P10159.	WGC-350x150	350 x 150	-	2000
P10160.	WGC-500x200	500 x 200	-	4000

UL certification for all WGC and WGS models, on demand

# Circutor



Residual current transformers

Code: P10151.

## Dimensions

×

