



WGC-30-SC, Residual current transformer

Code: P10182.

> Usefull diam.(mm): 30

> Cable (m): 0.5

> Max. Current (A): 63

Description

This new range features a series of improvements intended in particular for installing units on switchboards. Along with the usual attachment elements, this unit can be installed on DIN rails using an accessory, which facilitates its installation.

The residual current transformers of the **WGC** series offer better immunity to the transient current spikes that usually trigger the residual current protection. The residual current transformers of the WGC series have been designed to operate with the relays of the WGC series. The sensitivity (trip current) of the transformer-relay assembly is established by the associated relay.







Residual current transformers

Code: P10182.

Specifications

AC power supply, insulation		
Pulse test (kV)	3 kV	
Environmental characteristics		
Protection class	IP 20 (Terminals) IEC 60529	
Relative humidity (without condensation)	5 95 %	
Working temperature	-20 + 70 °C	
Mechanical characteristics		
Envelope	Self-extinguishing polycarbonate UL 94 V0	
Fastening	DIN rail with accessory	
Connection type	Cable length 0.5 (m)	
Weight (kg)	0,086	
Current measurement circuit		
Dynamic current (Idyn)	2,5 lth	
Permanent thermal current (Icth)	6 A	
Thermal short-circuit current (Ith)	1,8 kA / 1s	
Transformation ratio	30 / 0,06 A	
Maximum operating voltage (Um)	720 V	
Standards		
Electrical safety, Maximum height (m)	2000	
Electrical safety, Installation category	CAT III	
Standards	IEC 60664-1, IEC 60664-3, IEC 61869-2	
Measurement accuracy		

WGC

Residual current transformer

CODE	TYPE	Inner diameter (mm)	Cable (m)	In (A)	
P10181.	WGC-20-SC	20	0.5	63	
P10182.	WGC-30-SC	30	0.5	63	
P10131.	WGS-20	20	-	63	
P10132.	WGS-30	30	-	63	
P10151.	WGC-25	25	-	63	







Residual current transformers

Code: P10182.

CODE						
CODE	ТҮРЕ	Inner diameter (mm)	Cable (m)	In (A)		
P10152.	WGC-35	35	-	80		
P10153.	WGC-55	55	-	160		
P10154.	WGC-80	80	-	250		
P10155.	WGC-110	115	-	400		
P10156.	WGC-140	140	-	600		
P10157.	WGC-180	180	-	800		
P10158.	WGC-220x105	220 x 105	-	1250		
P10159.	WGC-350x150	350 x 150	-	2000		
P10160.	WGC-500x200	500 x 200	-	4000		

UL certification for all WGC and WGS models, on demand







Residual current transformers

Code: P10182.

Dimensions





Page 4 of 4