

WGS-20-TB



WGS-20-TB, Residual current transformer

Code: P11731.

- > Usefull diam.(mm): 20
- > I Δ n min.(A): 0.1
- > Max. Current (A): 63

Specifications

AC power supply, insulation

Pulse test (kV)	3 kV
-----------------	------

Mechanical characteristics

Size (mm) width x height x depth	46 x 60 x 32 (mm)
Envelope	Self-extinguishing polycarbonate UL 94 V0
Fastening	DIN rail with accessory
Connection type	Screw terminal (Pz type)
Weight (kg)	0,075

Environmental characteristics

Protection class	IP 20 (Terminals) IEC 60529
------------------	-----------------------------

Current measurement circuit

Dynamic current (I _{dyn})	2,5 I _{th}
Permanent thermal current (I _{cth})	6 A
Thermal short-circuit current (I _{th})	1,8 kA / 1s
Maximum operating voltage (U _m)	720 V

Standards

Standards	IEC 60664-1, IEC 60664-3, IEC 61869-2
-----------	---------------------------------------

Measurement accuracy

Accuracy	10 ... 15 %
----------	-------------

Differential protection

Type	Type B
------	--------

WGC-TB

Residual current transformers for type-B relays

CODE	TYPE	Inner diameter (mm)	I _n (A)
Only for RGU-10B			
P11731.	WGS-20-TB	20	63
P11751.	WGC-25-TB	25	63



WGS-20-TB

Residual current transformers for type-B residual current relays

Code: P11731.

CODE	TYPE	Inner diameter (mm)	In (A)
P11752.	WGC-35-TB	35	80
P11753.	WGC-55-TB	55	160
P11755.	WGC-80-TB	80	250
P11756.	WGC-110 TB	110	400
P11757.	WGC-140 TB	140	600
P11758.	WGC-180 TB	180	800



WGS-20-TB

Residual current transformers for type-B residual current relays

Code: P11731.

Dimensions

