



## WGC-25-TB

WGC-25-TB, Residual current transformer

Code: P11751.

- > Usefull diam.(mm): 25
- >  $I_{\Delta n}$  min.(A): 0.1
- > Max. Current (A): 63

### Specifications

#### AC power supply, insulation

Pulse test (kV)	3 kV
-----------------	------

#### Mechanical characteristics

Size (mm) width x height x depth	60.5 x 64 x 50 (mm)
Envelope	Self-extinguishing polycarbonate UL 94 V0
Fastening	DIN rail with accessory
Connection type	Screw terminal (Pz type)
Weight (kg)	0,12

#### Environmental characteristics

Protection class	IP 20 (Terminals) IEC 60529
------------------	-----------------------------

#### Current measurement circuit

Dynamic current ( $I_{dyn}$ )	2,5 $I_{th}$
Permanent thermal current ( $I_{cth}$ )	6 A
Thermal short-circuit current ( $I_{th}$ )	1,8 kA / 1s
Maximum operating voltage ( $U_m$ )	720 V

#### Standards

Standards	IEC 60664-1, IEC 60664-3, IEC 61869-2
-----------	---------------------------------------

#### Measurement accuracy

Accuracy	10 ... 15 %
----------	-------------

#### Differential protection

Type	Type B
------	--------

#### WGC-TB

Residual current transformers for type-B relays

CODE	TYPE	Inner diameter (mm)	$I_n$ (A)
P11731.	WGS-20-TB	20	63
P11751.	WGC-25-TB	25	63
P11752.	WGC-35-TB	35	80



# WGC-25-TB

Residual current transformers for type-B residual current relays

Code: P11751.

CODE	TYPE	Inner diameter (mm)	In (A)
P11753.	WGC-55-TB	55	160
P11755.	WGC-80-TB	80	250
P11756.	WGC-110 TB	110	400
P11757.	WGC-140 TB	140	600
P11758.	WGC-180 TB	180	800

Only for RGU-10B type relays



## WGC-25-TB

Residual current transformers for type-B residual current relays

Code: P11751.

## Dimensions

