



RGU-10, Residual current relay

Code: P11941. DESCATALOGADO

- > Módules: 3
- > Pre-alarm relay: Yes
- > N° relays: 1
- > I\(\Delta n \) (A): 0,03 ... 3 A | 0,03 ...30 A
- > Power supply (Vac): 230 Vac
- > Delay: 0,02 ... 10 s, INS, SEL
- > Mounting: DIN rail

Description

Electronic residual current protection relay of the **WG** series, connected to the external transformers of the **WG** / **WGC** series. Superimmunized type relay with high frequency currents filtering and high immunity. True RMS measurement (TRMS).

- O Data shown on the display
- o Features two independent programmable outputs (main and prealarm)
- o External input for remote-control functions (230 Vac)

Application

The RGU-10 relays associated with WG transformers offer smart residual current protection. Their design features guarantee maximum security and electrical service continuity, avoiding unwanted tripping.

Viewing the instantaneous leakage value on the display, together with the prealarm indicators, makes it possible to obtain information on the status of lines to be protected, and to perform adequate preventive maintenance.

In addition, version RGU-10 C features RS-485 communications and, with the PowerStudio software, offers centralised supervision in real time, as well as keeping a log of historical data for future analysis.







Electronic residual current relay compatible with external transformer of the WG series

Code: P11941.

Specifications

AC power supply	
Consumption	6 VA
Frequency	50/60 Hz
Nominal voltage	230 V~
Mechanical characteristics	
Size (mm) width x height x depth	52.5 x 85 x 67.9 (mm)
Fastening	DIN rail
Weight (kg)	0,234
Environmental characteristics	
Protection class	IP 20 (terminals), IP 41 (front)
Relative humidity (without condensation)	5 95 %
Ambient temperature	-40 +85 °C
Working temperature	-10 +50 °C
External reset input for tripping	
Туре	Optocoupled
Maximum power	0,7 W
Maximum voltage	230 Vca ± 20%
Standards	
Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300V ca
Standards	IEC 61008.1, IEC62020, IEC60947-2 Anexo M, IEC 60755
Electrical safety	
Insulation	Double-insulated electric shock protection class II (IEC 61010-1)
User interface	
Display type	Backlit LCD
Digital relay outputs	
Nominal load in AC	2500 VA
Nominal current	6 A ~
Nominal voltage	250 V ~
Maximum current	10 A ~
Mechanical life	10 × 10 ⁶







Electronic residual current relay compatible with external transformer of the WG series

Code: P11941.

Differential protection

Туре	Type A ultra-immunised
Sensitivity (I∆n), A	0,03 3 / 5-10-30 (Setup)
Transformer	External, WG/WGC series
Protection	
Circuit breaker type	Contactor or Circuit Breaker + trigger coil







Electronic residual current relay compatible with external transformer of the WG series

Code: P11941.

Dimensions Connections



