

RGE-R

RGE-R, Residual current relay

Code: P122320040000

> Módules: 2
> N° relays: 1
> IΔn (A): 0,03 ... 5 A
> Power supply (Vac): 24...48 Vac | 24...125 Vdc
> Delay: 0,02 ... 5 s (*1)
> Mounting: DIN rail

Description

Electronic residual current protection relay, used to connect to the residual current transformers WG / WGC Series. These electronic relays offer a high reliability, with the option of a fixed or adjustable sensitivity and delay Type A relay with high frequency current filtering and high immunity. Monitoring of the true root mean square (TRMS).

- Assembly on **DIN** rail **46277**
- Reduced size: 2 modules
- LED indicators:
  - Permanently lit leak indicator: LED Trigger relay
  - Flashing power LED and lit leak LED: detection of faults in the transformer's continuity
  - Flashing leak LED indicator:
    - Leak with a value under the value selected
    - 1 flash every 2s: 25 ... 50% of the leakage current
    - 1 flash every 1s: 50 ... 75%
    - 2 flashes every 1s: 75 ... <100%
    - Permanently: 100 %

Application

The relays of the RGE series and the transformer of the WG / WGC series enable a full residual current protection for both single and three-phase lines. They guarantee maximum security and continuity of the electrical service, avoiding unwanted tripping.



RGE-R

Electronic residual current relay

Code: P122320040000

Specifications

AC power supply

Installation category	CAT III 300 V
Consumption	3 VA
Frequency	50/60 Hz
Nominal voltage	24 ... 48 V~

DC power supply

Consumption	2,5 W
Nominal voltage	24 ... 125 Vdc (±15 %)

Mechanical characteristics

Size (mm) width x height x depth	35 x 85 x 68 (mm)
Envelope	Polycarbonate
Fastening	DIN 46276
Weight (kg)	0,056

Environmental characteristics

Protection class	IP 20
Relative humidity (without condensation)	5 ... 95 %
Working temperature	-10 ... +50 °C

Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300 V
Standards	IEC 60755, IEC 60947-2-M

Electrical safety

Insulation	Double-insulated electric shock protection class II (IEC 61010-1)

Digital relay outputs

Maximum current	10 A ~
Maximum power	2500 VA
Maximum switching capacity	2500 VA

Differential protection

Type	Type A ultra-immunised
Sensitivity (IΔn), A	0,03 ... 5 seleccionable
Delay time (tΔ)	0.02... 5 s (selectable)



RGE-R

Electronic residual current relay

Code: P122320040000

Protection

LED indication	Power supply voltage Earth leakage tripping External transformer disconnection Prealarm
Measure	True root mean square (TRMS)
Circuit breaker type	Contactor or Circuit Breaker + trigger coil

RGE-R
Ultraimmunized residual current relay, type A, for WGC transformer, 2 modules with visual prealarm.

CODE	TYPE	IΔn (A)	N° relays
P12231.	RGE-R1	0,03 ... 3 A	
P12A32.	RGE-RL	0,03 ... 5 A	1
P122320040000	RGE-R	0,03 ... 5 A	1

Requires a WGC residual current transformer To encode other parameters, such as the auxiliary power supply voltage, see the table at the end of the section

Creation date: 24/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



RGE-R

Electronic residual current relay

Code: P122320040000

Dimensions





Connections

