



## CBS-1600A

CBS-1600A, Multi-channel leakage current monitoring relay type A

Code: P12B01.

- > Protocol: Modbus/RTU
- > Módulos: 6
- > Pre-alarm relay: Yes
- > Communications: RS-485
- > N° relays: 2
- > N° Input channels: 16 (A)
- > Power supply: 230 V ~ ( $\pm 15\%$ )
- > Delay: 0,1-0,3-0,5-0,8-1-2-3-5 s
- > Sensitivity: 30 ... 3000 mA
- > Mounting: DIN rail

### Description

The **CBS-1600A** is an earth leakage current monitoring device that can be used to connect up to 16 type-A channels via transformers in the **WGC** range.

The device has a screen to display the 16 channels, 2 relays (alarm and pre-alarm) and RS-485 communications.

### Application

The **CBS-1600A** is suitable for installations with all neutral regimes: TT, TN and IT, where residual current monitoring is required.



# CBS-1600A

Type-A earth leakage monitoring relay with 16 channels

Code: P12B01.

## Specifications

### AC power supply

Installation category	CAT III 300V
Consumption	10 VA
Frequency	50 ... 60 Hz
Nominal voltage	230 V~ (± 15 %)

### Mechanical characteristics

Size (mm) width x height x depth	105 x 117.85 x 74 (mm)
Envelope	Self-extinguishing V0 plastic
Fastening	DIN rail
Weight (kg)	0,364

### Environmental characteristics

Protection class	IP 30, IP 40 (Front)  IK 08
Relative humidity (without condensation)	5 ... 95 %
Storage temperature	-20 ... +70 °C
Working temperature	-10 ... +50 °C

### Electrical characteristics

Conditional short-circuit current (Icc)	Depends on the circuit breaker
Sensor	Type A: WGC - WGS
Type	Type A (50 ... 60 Hz.)

### Digital inputs

Input impedance	2 kΩ
Input/output insulation	5.3 kV
Type	Potential-free contact

### Standards

Electrical safety, Maximum height (m)	2000
Electrical safety, Installation category	CAT III 300V ~
Electrical safety, Contamination level/class	2
Standards	IEC 62020-1

### User interface

LED	2
Keyboard	3 keys
Display type	LCD (negative)



# CBS-1600A

Type-A earth leakage monitoring relay with 16 channels

Code: P12B01.

## Digital relay outputs

Quantity	2
Maximum current	6 A
Maximum open contact voltage	230 V ~
Electrical life	$60 \times 10^3$ (250 V ~ / 5A)
Mechanical life	$10 \times 10^6$
Maximum switching capacity	1500 VA

## Differential protection

Delay time (tΔ)	0.1-0.3-0.5-0.8-1-2-3-5 s
-----------------	---------------------------

## Serial communication

Protocol	Modbus / RTU
Technology / Type	RS-485

## CBS-1600A

16 channel differential current control unit type A

CODE	TYPE	Nº relays	Nº Input channels	Communications	Protocol	Módulos	Pre-alarm relay	Power supply
P12B01.	CBS-1600A	2	16 (A)	RS-485	Modbus/RTU	6	Yes	230 V ~ (± 15%)

Associated with WGC-type residual current transformers



## CBS-1600A

Type-A earth leakage monitoring relay with 16 channels

Code: P12B01.

## Dimensions



## Connections

