



## WRN-22-0,3

WRN-22-0,3

Code: P14212. (CONSULTAR DISPONIBILIDAD)

- > Residual current relay
- > Usefull diam.(mm): 22
- > I $\Delta$ n (A): 0,3 A
- > Delay: 0,02 s

### Specifications

#### AC power supply

Frequency	50/60 Hz
Nominal voltage	230 V ~ $\pm$ 20 %

#### Mechanical characteristics

Size (mm) width x height x depth	52.5 x 85 x 68 (mm)
Fastening	DIN rail
Weight (kg)	0,146

#### Environmental characteristics

Protection class	IP 20 (terminals), IP 41 (rear panel)
Working temperature	-10 ... +50 °C

#### Standards

Standards	IEC 1008, IEC 255-5, UNE 801-2, UNE 801-3, UNE 801-4, UNE 60730-1
-----------	---

#### Other digital relay outputs

Nominal current	3 A ~
-----------------	-------

#### Digital relay outputs

Contact-coil insulation	2000 Vca
-------------------------	----------

#### Differential protection

Type	Type A
Sensitivity (I $\Delta$ n), A	0,3
Delay time (t $\Delta$ )	0,02 s
Transformer	Internal

#### Thermal-magnetic protection

Nominal voltage	230 V ~
-----------------	---------

#### Protection

Measure	True root mean square (TRMS)
Circuit breaker type	Circuit breaker + trigger coil