

IDA-EV-63-30, Residual current relay Type A

- Code: P17322.
- > Poles: 4
- > In (A): 63 A
- > Sensitivity: 30 mA + 6 mAdc
- > Mounting: DIN rail

Description

IDA-EV is a 6mA $_{DC}$ type-A RCCB with monitoring for use in electric vehicle chargers. Compact RCCB that provides residual current protection, with a sensitivity of 30 mA and 6 mA $_{DC}$ monitoring for use in electric vehicle charging stations. Available in 40 and 63 A nominal current gauges, for three-phase and single-phase connections. It guarantees adequate protection at electric vehicle charging points, in accordance with the **IEC 62955** standard.

Application

Device specifically designed to provide residual current protection of electric vehicle charging stations.





Type A RCCB with 6 mAdc monitoring

Code: P17322.

Specifications

AC power supply			
Frequency	50/60 Hz		
Nominal voltage	400 V ~ / 415 V ~		
Electrical characteristics			
Mechanical life	10000 operations		
Electrical lifetime	2000 cycles		
Mechanical characteristics			
Size (mm) width x height x depth	72 x 87.5 x 68 (mm)		
Envelope	Self-extinguishing V0 plastic		
Fastening	DIN rail (EN 60715, EN 50022)		
Weight (kg)	0,38		
Environmental characteristics			
Protection class	IP 20		
Relative humidity (without condensation)	5 95%		
Storage temperature	-40 +85 °c		
Working temperature	-25 +65 °C		
Current measurement circuit			
Nominal current (In)	63 A		
Standards			
Electrical safety, Maximum height (m)	2000		
Electrical safety, Installation category	CAT III, IEC 61010		
Standards	IEC 61008, IEC 62956		
Electrical safety			
Insulation	Double-insulated electric shock protection class II (IEC 61010-1)		
Differential protection			
Туре	Type A+6mAdc		
Sensitivity (I∆n), A	0,03		
Delay time (t∆)	Instantaneous or General (IEC 61008-1)		
Delay time (t∆)	Instantaneous or General (IEC 61008-1)		

IDA-EV RCCB with 6 mADC supervision type A

Circutor



Type A RCCB with 6 mAdc monitoring

Code: P17322.

CODE	ТҮРЕ	In (A)	Mounting	Poles	Sensitivity
P17321.	IDA-EV-40-30	40 A	DIN rail	4	30 mA + 6 mAdc
P17322.	IDA-EV-63-30	63 A	DIN rail	4	30 mA + 6 mAdc

Circutor



Type A RCCB with 6 mAdc monitoring

Code: P17322.

Dimensions

Connections

×

×

