



MCB.P C-2p-25A

MCB.P C-2p-25A, Circuit breaker

Code: P20215. [CONSULTAR DISPONIBILIDAD](#)

- > Poles: 2
- > In (A): 25 A
- > Curve: C

Description

MCB-P or **MCB-T** are circuit-breakers that combine the functions of a circuit breaker (overload and short-circuit protection) and those of a contactor on the same element. There are two options with **MCB**:

- Closed circuit-breaker: Allows remote control functions (contactor function). It can be disconnected and reconnected electrically with the adequate signal.
- Circuit-breaker opened by an overload or short-circuit trip or by manual disconnection: remote control reset is not allowed, only manually.

The remote control function works on the same contacts as those of the circuit breaker, guaranteeing the disconnection in each case. The **MCB-T** type includes a remote control module with two auxiliary, potential free (three-wire) contacts that indicate the status of the **MCB** at the input of the remote control (contactor function) and/or the circuit breaker.

Application

MCB are the perfect elements to guarantee self-reclosing residual current and overload protection applications, connected to WRKRT-25 relays.



MCB.P C-2p-25A

Circuit breaker

Code: P20215.

Specifications

AC power supply

| | |
|-----------|-------------|
| Frequency | 50 / 60 Hz. |
|-----------|-------------|

Mechanical characteristics

| | |
|----------------------------------|-------------------|
| Size (mm) width x height x depth | 54 x 90 x 68 (mm) |
| Weight (kg) | 0,26 |

Environmental characteristics

| | |
|------------------|-------------------------------|
| Protection class | IP 20 (according to DIN40050) |
|------------------|-------------------------------|

Digital relay outputs

| | |
|------------------------------|--------------------|
| Maximum current | 0,5 A |
| Maximum open contact voltage | 230 V ~ |
| Mechanical life | > 20000 operations |

Differential protection

| | |
|----------------------|----|
| Sensitivity (IΔn), A | 25 |
|----------------------|----|

Thermal-magnetic protection

| | |
|------------------|---------------|
| Trip curve, Type | C |
| Nominal voltage | 210 / 240 V ~ |

Only for operation with WRU-10K C curve circuit breaker with a 6 kA cut off power (IEC 60898); optional D curve (up to 32 A), for an additional charge of 10%



MCB.P C-2p-25A

Circuit breaker

Code: P20215.

Dimensions

