

# MT-TS- 250A- 3P

MT-TS-250A-3P, Motorised MCB, 3 poles

Code: P20H64.

> Poles: 3

> In (A): 250 A

## Description

**MT-TS** series automatic switch with remote control for currents from 80 to 630A, with both 3 and 4 poles. Provides short-circuit and overload protection, and is also used as a circuit breaker.

The switch can be reconnected in two ways, depending on how the operation mode is set in the motor group:

- "MANU": done manually on the switch itself by turning it to OFF and then ON.
- "AUTO": done by means of an electrical impulse that follows the OFF-ON sequence.

## Application

The **MT-TS** series are motorized automatic switches that can be operated remotely and are valid for any application that requires remote connection/disconnection. They are an essential component for providing overload protection with reclosing.



Creation date: 22/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



# MT-TS- 250A- 3P

Motorised circuit-breaker

Code: P20H64.

## Specifications

### DC power supply

| | |
|---|---|
| Nominal voltage | 500 V |

### Electrical characteristics

| | |
|---|---|
| Mechanical life | 25000 cycles |
| Electrical lifetime | 10000 cycles 415 V In |
| Insulation voltage, circuit | 1000 V |

### Mechanical characteristics

| | |
|---|---|
| Size (mm) width x height x depth | 105 x 160 x 195 (mm) |
| Weight (kg) | 3,6 |

### Environmental characteristics

| | |
|---|---|
| Protection class | IP20, IEC 60529 |
| Storage temperature | -40 ... +70 °C |
| Working temperature | -20 ... +70 °C |

### Standards

| | |
|---|---|
| Electrical safety, Contamination level/class | Pollution resistance 3 |
| Standards | IEC 60947-2, IEC 60664-1 |

### Circuit breaker / RCCB

| | |
|---|---|
| Assigned frequency (Hz) | 50 / 60 Hz |
| Rated nominal voltage (Un) | 690 V ~ |

### Thermal-magnetic protection

| | |
|---|---|
| Magnetic adjustment (Ii) | Fixed 10 x In |
| Thermal adjustment (Ir) | Adjustable, 3 settings: 0.8 / 0.9 / 1 x In |
| Rated short-circuit marking capacity (IEC 60947-2) (Icm) | 220 kA at 220/240 Vac 50/60 Hz. 105 kA at 380/415 Vac 50/60 Hz. 105 kA at 440/460 Vac 50/60 Hz. 88 kA at 480/500 Vac 50/60 Hz. 46 kA at 525 Vac 50/60 Hz. 17 kA at 660/690 Vac 50/60 Hz. |
| Nominal current In (A) | 250 |
| Ultimate short-circuit breaking capacity (Icu) / service short-circuit breaking capacity (Ics), in DC (IEC 60947-2) | 50 kA at 250 Vdc, reference 50 kA at 500 Vdc (2poles in series), reference |
| AC ultimate short-circuit breaking capacity (Icu) (IEC 60947-2) | 100 kA at 220/240 Vac 50/60 Hz. 50 kA at 380/415 Vac 50/60 Hz. 50 kA at 440/460 Vac 50/60 Hz. 42 kA at 480/500 Vac 50/60 Hz. 22 kA at 525 Vac 50/60 Hz. |

### Protection

| | |
|---|---|
| Circuit breaker type | Class A |



Creation date: 22/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.



# MT-TS- 250A- 3P

Motorised circuit-breaker

Code: P20H64.

**MT-TS**
Motorised circuit-breaker

| CODE | TYPE | Poles | In (A) |
|---|---|---|---|
| **3 poles** | | | |
| P20H60. | MT-TS- 80A- 3P | 3 | 80 A |
| P20H61. | MT-TS- 100A- 3P | 3 | 100 A |
| P20H62. | MT-TS- 125A- 3P | 3 | 125 A |
| P20H63. | MT-TS- 160A- 3P | 3 | 160 A |
| P20H64. | MT-TS- 250A- 3P | 3 | 250 A |
| P20H65. | MT-TS- 400A- 3P | 3 | 400 A |
| P20H66. | MT-TS- 630A- 3P | 3 | 630 A |
| **4 poles** | | | |
| P20H70. | MT-TS- 80A- 4P | 4 | 80 A |
| P20H71. | MT-TS- 100A- 4P | 4 | 100 A |
| P20H72. | MT-TS- 125A- 4P | 4 | 125 A |
| P20H73. | MT-TS- 160A- 4P | 4 | 160 A |
| P20H74. | MT-TS- 250A- 4P | 4 | 250 A |
| P20H75. | MT-TS- 400A- 4P | 4 | 400 A |
| P20H76. | MT-TS- 630A- 4P | 4 | 630 A |

Fixed magnetic and adjustable thermal protection


Creation date: 22/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.




# MT-TS- 250A- 3P

Motorised circuit-breaker

Code: P20H64.

## Dimensions






Creation date: 22/11/2026 - CIRCUTOR, SAU reserves the right to make technical changes or modify the content/images of this document without prior notice, in order to improve its reliability, functionality, design or for other reasons.
It accepts no liability for any errors, inaccuracies or possible lack of information in this document.