



MT-TS- 400A- 3P

MT-TS-400A-3P, Motorised MCB, 3 poles

Code: P20H65.

> Poles: 3

> In (A): 400 A

Description

MT-TS series automatic switch with remote control for currents from 80 to 630A, with both 3 and 4 poles. Provides short-circuit and overload protection, and is also used as a circuit breaker.

The switch can be reconnected in two ways, depending on how the operation mode is set in the motor group:

- "MANU": done manually on the switch itself by turning it to OFF and then ON.
- "AUTO": done by means of an electrical impulse that follows the OFF-ON sequence.

Application

The **MT-TS** series are motorized automatic switches that can be operated remotely and are valid for any application that requires remote connection/disconnection. They are an essential component for providing overload protection with reclosing.



MT-TS- 400A- 3P

Motorised circuit-breaker

Code: P20H65.

Specifications

DC power supply

| | |
|-----------------|-------|
| Nominal voltage | 500 V |
|-----------------|-------|

Electrical characteristics

| | |
|-----------------------------|-----------------------|
| Mechanical life | 25000 cycles |
| Electrical lifetime | 10000 cycles 415 V In |
| Insulation voltage, circuit | 1000 V |

Mechanical characteristics

| | |
|----------------------------------|------------------------|
| Size (mm) width x height x depth | 140 x 260 x 268.5 (mm) |
| Weight (kg) | 7 |

Environmental characteristics

| | |
|---------------------|-----------------|
| Protection class | IP20, IEC 60529 |
| Storage temperature | -40 ... +70 °C |
| Working temperature | -20 ... +70 °C |

Standards

| | |
|--|--------------------------|
| Electrical safety, Contamination level/class | Pollution resistance 3 |
| Standards | IEC 60947-2, IEC 60664-1 |

Circuit breaker / RCCB

| | |
|----------------------------|------------|
| Assigned frequency (Hz) | 50 / 60 Hz |
| Rated nominal voltage (Un) | 690 V ~ |

Thermal-magnetic protection

| | |
|---|--|
| Magnetic adjustment (Ii) | Fixed 10 x In |
| Thermal adjustment (Ir) | Adjustable, 3 settings: 0.8 / 0.9 / 1 x In |
| Rated short-circuit marking capacity (IEC 60947-2) (Icm) | 220 kA at 220/240 Vac 50/60 Hz. 143 kA at 380/415 Vac 50/60 Hz. 143 kA at 440/460 Vac 50/60 Hz. 88 kA at 480/500 Vac 50/60 Hz. 46 kA at 525 Vac 50/60 Hz. 17 kA at 660/690 Vac 50/60 Hz. |
| Nominal current In (A) | 400 |
| Ultimate short-circuit breaking capacity (Icu) / service short-circuit breaking capacity (Ics), in DC (IEC 60947-2) | 50 kA at 250 Vdc, reference 50 kA at 500 Vdc (2poles in series), reference |
| AC ultimate short-circuit breaking capacity (Icu) (IEC 60947-2) | 100 kA at 220/240 Vac 50/60 Hz. 65 kA at 380/415 Vac 50/60 Hz. 65 kA at 440/460 Vac 50/60 Hz. 42 kA at 480/500 Vac 50/60 Hz. 22 kA at 525 Vac 50/60 Hz. |

Protection

| | |
|----------------------|---------|
| Circuit breaker type | Class A |
|----------------------|---------|



MT-TS- 400A- 3P

Motorised circuit-breaker

Code: P20H65.

MT-TS

Motorised circuit-breaker

| CODE | TYPE | Poles | In (A) |
|----------------|-----------------|-------|--------|
| 3 poles | | | |
| P20H60. | MT-TS- 80A- 3P | 3 | 80 A |
| P20H61. | MT-TS- 100A- 3P | 3 | 100 A |
| P20H62. | MT-TS- 125A- 3P | 3 | 125 A |
| P20H63. | MT-TS- 160A- 3P | 3 | 160 A |
| P20H64. | MT-TS- 250A- 3P | 3 | 250 A |
| P20H65. | MT-TS- 400A- 3P | 3 | 400 A |
| P20H66. | MT-TS- 630A- 3P | 3 | 630 A |
| 4 poles | | | |
| P20H70. | MT-TS- 80A- 4P | 4 | 80 A |
| P20H71. | MT-TS- 100A- 4P | 4 | 100 A |
| P20H72. | MT-TS- 125A- 4P | 4 | 125 A |
| P20H73. | MT-TS- 160A- 4P | 4 | 160 A |
| P20H74. | MT-TS- 250A- 4P | 4 | 250 A |
| P20H75. | MT-TS- 400A- 4P | 4 | 400 A |
| P20H76. | MT-TS- 630A- 4P | 4 | 630 A |

Fixed magnetic and adjustable thermal protection



MT-TS- 400A- 3P

Motorised circuit-breaker

Code: P20H65.

Dimensions

